INDEX TO VOLUME 44

SUBJECTS

(N) denotes Note on Experimental Technique and Apparatus, (L) Letter to the Editor

cid saw for strain-free cutting of single crystals (N) 230
coustics, underwater: Physics Exhibition discourse 709
dhesive joints, methods for constructing and apparatus for measuring shear strength at high temperatures 457
erosols, anemonetric isokinetic sampling probe 249
loys, measurement of optical properties in ultra-high vacuum 997
uminium lines, 800 Å wide, fabricated using an electron beam (N) 231
uminized surfaces, testing by surface-coated reference flats of the Fizeau interferometer 899
mplifier, fluidic wall-attachment, of improved sensitivity 683
mplifier, high input impedance, low level d.c., utilizing a solid-state operational amplifier (N) 870
mplifier, power, low-frequency, simple over-voltage protection device (N) 560
nalysis *see* Isotopic analysis, Size analysis
nemometer, constant temperature hot-wire 363
ngles, small, phototransducer for measuring (N) 479
nisotropic susceptibilities, new method of measuring using sample holder with two degrees of freedom 446
spherical surfaces in optics, measurement 1005
urora, high luminosity spectrograph for recording the far ultra-violet spectra 357

affle, ring focus, photofabrication, for a lens β spectrometer (N) 474
eam of variable energy, electron optical systems with fixed image positions 993
eam envelope and particle track, small versatile analogue computer 697
eam *see also* Electron beam, Reactor beam
eta source, radioactive, used to monitor high airborne-dust concentrations (N) 562
othermal radiometer: selection 847
tumens, apparatus for measuring dynamic elastic properties 375
ack-body cavity for the calibration of radiation pyrometers (N) 221
oiler furnaces, use of heat flux meter 371
ourdon gauges, behaviour at elevated temperatures (N) 866
rewster angle, windows set near for optical transmission 720
ridge, coaxial with helical line sample holders as an n.q.r. detector 911
ridge for measurement of permittivity and loss up to 5 GHz (N) 401
ridge, multivibrator, for temperature measurement 531
ridge *see also* Thermistor bridge
rightness, apparent, instrument for interocular matching 413

alorimeter, accurate carbon cone, for pulsed lasers 835
alorimetry, thermistor bridge (N) 290
amera, x-ray powder, small bulk specimen holder (N) 1041
apacitor, precision micrometer (N) 59
arbon cone calorimeter for pulsed lasers 835
arbon dioxide content of air, monitoring by laser action in human breath (N) 408
arbon monoxide gas, detection and measurement of dangerous quantities (N) 642
athode lamps, hollow, modulator used in atomic absorption spectroscopy (N) 1050
avity forces: weighing of samples with rough surfaces 275
ell, infra-red, for studying adsorbed species at gas–solid interface (N) 872
entrifuge, high temperature, for phase equilibrium studies in molten salts 454
Channel mutliplier life tests in ultra-high vacuum (N) 1053
Characteristic curves for optically pumped lasers automatic tracer (N) 309
Chart recorder, potentiometric, with trace cutting attachment (N) 293
Chemical indicator solutions used for flow visualization (N) 558
Chopper, vacuum reed, self-maintained 639
Chromotographic analysis, gas–liquid, of irradiated compounds, sample injection port (N)1031
Chromotography *see* Gas chromotography
Chronometer, accurate and synchronizing (N) 476
Coils, square cross sections, for the production of uniform magnetic fields 755
Compressive testing at temperatures up to 1800°C, instrumental modifications 366
Computer, analogue, for particle track and beam envelope 697
Computer of average transients, use in the study of rapidly changing spectra 821
Computer systems, on-line, for processing high resolution mass spectral data 343
Conductance cell, electrolytic, for use at elevated temperatures and pressures (N) 1037
Conductivity measurements, by multi-range recorder with a linear scale (N) 878
Conductor movement, in a homegeneous magnetic field, possibility of detection (L) 316, (L) 815
Conductors, solid nonmetallic electrical contact (N) 645
Connector, plug and socket, simple 50 kv feed-through (N) 1056
Control system for a fully automatic pressure scanned Fabry-Pérot interferometer 360
Cooling systems, flood protection device (N) 305
Coulter counter, experimental indication of volume proportional response for irreugularly shaped particles (N) 648
Counter, large-area whole-body, performance 499
Counter, proportional, locus sensitive 203
Counter, proportional, new formula for gas amplification (N) 395
Counter, proportional point anode, for the detection of soft x-rays in microanalysis 983
Counter, whole-body animal, using a liquid scintillator 495
Cracks in massive bodies, examination by the transmission electron microscope (N) 234
Cryopumps for use in low temperature control (N) 68
Cryostat, metal immersion, for optical studies at temperatures down to 2°K 271
Cryostat, versatile, for the study of point defects in quenched metals (N) 161
Crystal anisotropy in magnetic films, novel method for measurement (N) 181
Crystal growing systems, continuous flow, introduction of trace amounts of dopant gases (N) 176
Cystal holder, rotatable low temperature, for n.m.r. studies (N) 1028
Crystal studies, automatically controlled rotating head (N) 869
Crystal transformation, detection of changes of lattice parameters around the interface (N) 812
Crystal wafer orientation by proton channelling (N) 880
Crystallographic apparatus, improved goniometer head base (N) 178
Crystals, device for accurate orientation and fabrication (N) 1042
Crystals, lead stearate, optimization for diffraction of ultra soft x-rays 976
Crystals, single, acid saw for strain-free cutting (N) 230
Crystals, single, precision polishing of layer (N) 159
Current meters and turbine-type flowmeters, method of measuring time constants 17

Current pulses, monitored by inductively loaded probe (N) 555
Current regulator, self-balancing, for measurement of critical currents of superconductors (N) 793
Cylinder bores, comparison by holography 489

Damping at constant amplitude, continuous recording (N) 169
Dark current and noise, reduction in photomultiplier tubes by magnetic defocussing (N) 182
Density, apparent, of lump solids, apparatus for determination at elevated temperatures (N) 568
Density of gas, measurement by natural damping of a vibrating reed 385
Density current measurements, laboratory, use of Bagnold's velocity meter 37
Density determinations on small liquid samples 382
Detector, condenser microphone infra-red, frequency response characteristics 731
Detector, room temperature, for use with carbon dioxide lasers 629
Diamond, semiconducting, pulse method for measuring electrical resistance (N) 296
Die, PTFE, for pressing high purity materials (N) 565
Dielectric constant, phase-locking method of measuring (N) 557
Differential thermal analysis of materials with very volatile components (N) 399
Diffraction grating calculator (N) 795
Diffraction *see also* Electron diffraction, X-ray diffraction
Diffractometer *see* X-ray diffractometer
Domain structure and magnetic fields, direct observation in the scanning electron microscope 889
Dopant gases, introduction of trace amounts into continuous flow crystal growing systems (N) 176
Dosimetry, thermoluminescence, measuring device 939
Dosimetry systems, integrating thermoluminescent, improved method of adjusting heating conditions (N) 481
Drawing apparatus, glass fibre (N) 864
Droplets, stationary, apparatus for study of reactions by radioactive tracers 936
Drying system and glove-box for the manipulation of moisture sensitive material (N) 658
Dust concentrations, high, use of a radioactive beta source for monitoring (N) 562
Dust samples, measurement of projected area (N) 217
Dynamic elastic properties of bitumens, apparatus for measuring 375
Dynamic stiffness of roads and soils, apparatus for measuring 537
Dynamic testing of a parallel wire resistance water wavemeter (N) 803

Earth pressure cell, influence of diaphragm flexibility on performance 781
Editorial 1
Elastic constants of solidified gases and liquids by a strain gauge technique (N) 179
Electrical conductivity, notes on the experimental application to tracer detection in fluid flow systems (N) 858
Electrical contacts to solid nonmetallic conductors (N) 645
Electrical properties of insulators, examination by surface charge measurement 521
Electrical resistance of semiconducting diamond, pulse method for measuring (N) 296
Electrical resistivity, athermal and isothermal, device for studies in the range −186 to 400°C (N) 75
Electrical resistivity, versatile cryostat for studies on quenched metals (N) 161
Electrode, double barrelled micropipette, simple method of fabricating (N) 549
Electrode, gauging, use of guarded sphere in length metrology 931
Electromagnetic calibration coil for a Willmore Mk 11 seismometer (N) 1035
Electrometer, tube holder with built-in negative feedback capacitor (N) 74
Electron beam currents, measurement (N) 61
Electron beam formation of 800Å wide aluminium lines (N) 2
Electron beam profile indicator (N) 800
Electron bombardment evaporation source for powdered mater (N) 70
Electron diffraction, improved technique for ultra-high resoluti (N) 867
Electron diffraction apparatus, combined low energy and reflecti high energy 686
Electron energy distribution functions, effect of a.c. amplitude measurement 517
Electron image information store, dynamic (L) 153
Electron impact producing kinetic energy of fragment ions 336
Electron irradiation vessels, fast, thin glass windows (N) 306
Electron microprobe instruments, stereoscopic display syste (N) 294
Electron microscope, 500 kv, functional features 747
Electron microscope, improved standard specimen for alignme (N) 1036
Electron microscope, mirror, using magnetic lenses 893
Electron microscope, scanning direct observation of doma structure and magnetic fields 889
Electron microscope, scanning specimen cooling stage (N) 806
Electron microscope, Siemens, improved Valdré-type tilting hold (N) 303
Electron microscope, Siemens Elmiscop I, specimen airlo chamber 681
Electron microscope, thickness measurement (N) 61
Electron microscope, transmission, used for examination of crac formed in massive bodies (N) 234
Electron microscope holders for viewing thin wire specimens ar fie d-ion microscope tips (N) 238
Electron microscope specimen holder for simultaneous strainin tilting and rotating of thin foils (N) 289
Electron microscope specimens, tungsten shadow casting 207
Electron microscopy, transmission, chemical thinning techniq for simultaneous preparation of foils: application to YA (N) 862
Electron microscopy, transmission, preparation of thin foils titanium and titanium alloys (N) 63
Electron microscopy, transmission, preparation of thin glass film (N) 216
Electron microscopy, transmission, preparation of thin metal fo from a small specimen (N) 550
Electron microscopy, transmission, rapid measurement of thickne during preparation of disk specimens (N) 292
Electron microscopy, transmission, simple method of preparin thin metal foils (N) 297
Electron optical systems with fixed image positions for beams variable energy 993
Electron paramagnetic resonance *see under* Spectrometer
Electron physics at the Physics Exhibition 673
Electron spin resonance, helical resonators 509
Electron spin resonance instrumentation, 100 kHz component transistor circuit design (L) 882
Electron spin resonance spectrometer, sensitive 8 mm, using doub sideband demodulation 354
Electron spin resonance spectroscopy, improved circuit technique (N) 403
Electron spin resonance *see also under* Spectrometer
Electron temperature variation, direct display in moving striation 1023
Electronic instruments at the Physics Exhibition 672
Energy distributions, functions of electrons, effect of a.c. amplitud on measurement 517
Energy output of laser, absolute method for measuring (N) 468
Erosion rates in material, detection by microwaves 699
Etalon, Fabry-Pérot (N) 646
Evaporation filament with automatic cut-off (N) 166
Excitation cross sections, determinations by semi-automati monochromator 153

Fabry-Pérot etalon, simple stable (N) 646
Fabry–Pérot fringe splitter, ten-channel fibre optic 26

Ferromagnetic materials, automatic swept-frequency spin-echo spectrometer for n.m.r. 761
Fibre optic Fabry–Pérot fringe splitter, ten-channel 26
Fibres, electronic device for spherical averaging of x-ray scattering (N) 236
Field, homogeneous, design of air-core magnet for generation 636
Field ion micrographs, method for indexing 828
Field ion microscope, all-metal, cryogenically pumped (N) 167
Field-ion, microscope, automatic electropolishing supervisor for preparing specimens (N) 808
Field-ion microscope, photography of images (N) 223
Field ion microscope, preparation of contamination-free tungsten specimens (N) 1044
Field-ion microscope, pumped by sputter-ion pumps, gas contamination (N) 802
Field ion microscope, ultra-high vacuum, specimen transfer device 692
Field-ion microscope tips, holders for viewing by the electron microscope (N) 238
Field modulation effect in rubidium magnetometer 618
Filament, evaporation, with automatic cut-off (N) 166
Film thickness monitor, versatile and of high accuracy 917
Films, magnetic, novel method for measurement of crystal anisotropy (N) 181
Films, metal, some fundamental problems of sticking probabilities of gases 327
Films, thick, interferometric method for measuring thickness (N) 393
Films, thin absorbing, containing pinholes, optical transmission (N) 805
Films, thin glass, preparation for electron microscopic examination by direct transmission (N) 216
Filters, balanced, use for x-ray diffraction 736
Flame, measurement of gas velocity (N) 227
Flash photolysis and time resolved mass spectrometry, apparatus for 422
Flaws, detection by microwaves 699
Flood protection device for cooling systems (N) 305
Flow switches, glass, (N) 173
Flowmeter, miniature turbine, for low flow rates 12
Flow visualization, technique using chemical indicator solutions (N) 558
Flow visualization in water: a review of techniques 2
Flowmeter, turbine-type, and current meter, method of measuring time constants 17
Flowmeter *see also* Microflowmeter
Fluid flow systems, notes on the experimental application of electrical conductivity to tracer detection (N) 858
Fluid mechanics: use of ruby laser with interferometers 1015
Foils, metal, method of making thin slits (N) 1043
Foils, thin, irradiated in reactor beam, automatic system for rapid measurement 766
Foils, thin, straining, tilting and rotating by electron microscope specimen holder (N) 289
Foils, thin, of titanium and titanium alloys for transmission electron microscopy (N) 63
Foils, thin metal, simple method for preparing for ttansmission electron microscopy (N) 297
Foils for transmission electron microscopy, chemical thinning technique for simulatneous preparation: application to YAG (N) 862
Foils *see also* Metal foils
Fowler–Nordheim plots, fast recording of data (N) 1051
Fracture tests, photographic method for the recording of specimen behaviour (N) 873
Frequency modulation, use of brushless synchros 440
Frequency shifter, 100 kHz, adjustable in steps of 1 in 10^{10} (N) 300
Frost damage to road making materials, apparatus for testing resistance (N) 553
Furnace, high-temperature, for a single x-ray diffractometer (N) 183
Furnace, rotating wall, d.c.–arc plasma 525
Furnace designed for very uniform temperatures 257
Furnace controllers converting on–off to proportional operation (N) 81

Galvanic skin response, apparatus for measurement 50
Gas, density measurement by natural damping of a vibrating reed 385
Gas, liquefied, centrifugal pumping (N) 469
Gas, on metal films, some fundamental problems in measurement of sticking probabilities 327
Gas admission to evacuated systems, simple mercury cut-off (N) 295
Gas amplification in a proportional counter, new formula (N) 395
Gas analysers, non-dispersive infra-red, cross-sensitivity using condenser microphone detectors 189
Gas chromotography using fast scan mass spectrometry 676
Gas chromatography, precision method for measurement of small time intervals (N) 1046
Gas circulating pump, double-acting all-glass (N) 388
Gas circulation pump for laboratory use (N) 213
Gas cold trap, electrically insulating (N) 312
Gas contamination in a field-ion microscope pumped by sputter-ion pumps (N) 802
Gas measurement system, improved automatic Toepler pump (N) 1033
Gas velocity in a flame, measurement (N) 227
Gas volumes, large, determination of mass by direct weighing 788
Gauge, maximum pressure differential (N) 307
Gauge, quartz spoon, behaviour at elevated temperatures (N) 866
Gauge *see also* Ionization gauges, McLeod gauge
Gelation timer–viscometer, laboratory (N) 963
Glass blowing torch, dual purpose (N) 302
Glass demountable circulation pump with variable high pumping speed (N) 860
Glass fibre drawing apparatus (N) 864
Glass filaments for surface studies (N) 228
Glass windows, thin, for use in fast electron irradiation vessels (N) 306
Glove-box and drying system for the manipulation of moisture sensitive material (N) 658
Goniometer head for adjustment of single crystals for x-ray diffraction (N) 643
Goniometer head base, improved, for use on crystallographic apparatus (N) 178
Gratings, plastic radial, for use with an optical incremental shaft resolver 146
Gratings, radial, dividing engine of high accuracy 899
Gratings *see also under* Diffraction grating

Halide-disk holder, modified, for infra-red spectrometry (N) 168
Harmonic generator, plasma–metal junction, high speed constant current switch (N) 406
Heat flux, simple method for measuring 541
Heat flux meter for use in boiler furnaces 371
Helium, liquid *see* Liquid helium
High-pressure intensifiers, axially ported (N) 396
High pressure ionization gauge 969
High temperature phase changes, magnetic device for detection 200
Holographic velocity measurement (N) 1032
Holography, application to the comparison of cylinder bores 489
Holography, three-dimensional, of phase objects, scope and limitations 1011
Humidities, ultra-low, plant use of a pressurized Goldsmith–Cox hygrometer (N) 84
Hygrometer, electrolytic, Goldsmith–Cox, investigation of accuracy at the 10^{-6} atm level (N) 87
Hygrometer, electrolytic, improved 29
Hygrometer, pressurized Goldsmith–Cox for plant use at ultra-low humidities (N) 84

Impedance measurements in polarography: apparatus for accurate wide frequency work 843

Indium antimonide, photoconductive, spark-machining 973
Information store, dynamic electron image (L) 153
Infra-red cell for studying adsorbed species at gas–solid interface (N) 872
Infra-red detectors, condenser microphone, frequency response characteristics 731
Infra-red detectors by spark-machining of indium antimonide 973
Infra-red gas analysers, non-dispersive, cross-sensitivity effects using condenser microphone detectors 189
Infra-red pyrometer for the measurement of nylon threadline temperatures (N) 1048
Infra-red radiation detection by the pyroelectric effect 694
Infra-red radiation pyrometer 988
Infra-red reflectivity of micro-samples, method for measuring (N) 65
Infra-red spectrography, cell for study of adsorption (N) 961
Instron machines, self-aligning grip system and tensile specimens (N) 389
Insulators, examination of electrical properties by surface charge measurement 521
Integrator, electronic digital (N) 959
Intensifiers, high pressure, axially ported (N) 396
Interference, pulses, suppression in radiation experiments (N) 792
Interferometer, Fabry–Pérot fully automatic pressure scanned, control system 360
Interferometer, Fizeau, surface-coated reference flats for testing fully aluminized surfaces 899
Interferometer, use with a ruby laser for work in fluid mechanics 1015
Interferometric method for measuring the thickness of thick films (N) 393
Interferometry, laser streak, optics 725
Ionization gauge, Bayard–Alpert, with grid end-caps, modulation 927
Ionization gauge, high pressure 969
Ions, fragment, kinetic energy produced by electron impact 336
Irradiation, simultaneous, by photochemical reactor (N) 485
Isotope ratio measurement by peak matching 774
Isotopic abundance ratio measurements on strontium with a mass spectrometric dual collector 141
Isotopic analysis of rhenium from a thermal ionization source 769

Joints *see* Adhesive joints

Kerr cell system for measurement of high voltage transient waveforms 688
Kinetic energy of fragment ions produced by electron impact 336

Laboratory operations, sequential, improved programmed controller 831
Laser, absolute method for measuring energy output (N) 468
Laser, carbon dioxide, simple room temperature detector 629
Laser, continuous wave, measurement of radiation (N) 218
Laser, continuous wave, water-cooled mercury arc for pumping 273
Laser He–Ne, reactivation by diffusion (N) 312
Laser, indium arsenide, used for measurement of time constants of some fast photodetectors 419
Laser, optically pumped, automatic tracer of characteristic curves (N) 309
Laser, pulsed, accurate carbon cone calorimeter 835
Laser, ruby, comparison of rotating mirror and liquid bleacher as a *Q* switch (N) 548
Laser, ruby, use with interferometers suitable for work in fluid mechanics 1015
Laser action in human breath and its use for monitoring the CO_2 content of air (N) 408
Laser cavities, liquid 947
Laser light, plasma-scattered, 12-channel Doppler-profile spectrophotometer 691
Laser modes, high power CO_2, dynamic viewing (N) 1045
Laser streak interferometry, optics 725
Lattice parameters, detection of changes around the interface in crystal transformation (N) 812
Lattice *see also under* Square lattice
Leaks, calibrated equipment especially adapted for substances wi melting points above room temperature (N) 954
Length determination, o–soft, precise and automatic 465
Length metrology, use of guarded sphere as a gauging electro 931
Light modulators, coupled, used with optical shaft resolver 269
Liquid helium cooled trap for ultra-high vacuum (N) 73
Liquid laser cavities 947
Liquid nitrogen transfer system, automatic 156
Liquid phases, conductive, measurement of contact potenti difference by capacitor method 443
Liquid samples, small, determination of density 382
Liquid scintillator used for whole-body animal counter 495
Liquids, use of pressure bar to measure transient stresses (N) 5
Liquids, readings of small pressure differences 254
Low pressure measurement with thermistors (N) 83
Low temperature control, cryopump (N) 68
Low temperature techniques at the Physics Exhibition 671
Low temperatures, device for measurement of sound propagatic constants 136

Machining device, spark erosion (N) 1058
McLeod gauge, mercury reservoir (N) 652
Magnet, air-core, designed for the generation of homogeneo fields 636
Magnetic field and domain structure, direct observation in t scanning electron microscope 889
Magnetic field, homogeneous, possibility of detection of a condu tor movement (L) 316, (L) 815
Magnetic field, small, Hall effect magnetometer (N) 798
Magnetic field, uniform, square cross section coils for productic 755
Magnetic probe, optical 265
Magnetic recording system, digital 625
Magnetometer, field tracking, for the range 2000–4500 Oe (N) 4
Magnetometer, Hall effect, for small magnetic fields (N) 798
Magnetometer, proton free-precession for locating buried magne (N) 552
Magnetometer, rubidium, stray field modulation effect 618
Magnetometer, torque, for use at high pressures 621
Magnetometer, vibrating sample, for use between 4 and 1000 133
Magnetotelluric observatory digital portable 943
Magnetron pulse current, simple pulse current transformer fo checking (N) 71
Magnets, buried, proton free-precession magnetometer for locatin (N) 552
Magnets, superconducting, magnetic field sweep (N) 949
Manometer, micro 852
Mammalian nervous tissue, isolated, chamber for maintainin during electrical recording 1025
Mass of large gas volumes, determination by direct weighing 7
Mass spectrographs, design for improvement of sensitivity (L) 8
Mass spectrometer, AEI MS2H, mass marker 209
Mass spectrometer, on-line computer system for processing hig resolution data 343
Mass spectrometer, peak switching, with automatic voltage scanne 427
Mass spectrometer, photoionization sources 283
Mass spectrometer, small, 180° fast scanning 587
Mass spectrometer, tandem, improved abundance sensitivity b means of a retardation lens (N) 956
Mass spectrometer inlet leak (N) 871
Mass spectrometric dual collector for precise strontium isotop abundance ratio measurement 141
Mass spectrometry, fast scan, applied to gas chromotography 67
Mass spectrometry, time resolved, and flash photolysis, apparatu for 422
Materials and components at the Physics Exhibition 670
Materials, high purity, PTFE die for pressing (N) 565

Mercury arc, water-cooled, for continuous wave laser pumping 273
Mercury cut-off for use in gas admission to evacuated systems (N) 295
Metal foil windows, gas-tight (N) 392
Metal foils, thin, preparation from a small specimen for use in electron microscopy (N) 550
Metal fumes, atomic absorbtion method for measurement 678
Metal immersion cryostat for optical studies at temperatures down to 2°K 271
Metal–quartz sealed window, bakeable (N) 174, (L) 1059
Metal wires, recording of accurate Snoek spectra at low frequencies (N) 810
Metals, quenched, versatile cryostat for the study of point defects (N) 161
Metals *see also under* Foils
Microanalysis, detection of soft x-rays by point anode proportional counters 983
Microbalance technique: cavity forces 275
Micrographs, field ion, method for indexing 828
Microflowmeter, theoretical consideration 1018
Micrometer capacitor, precision (N) 59
Microscope for use at temperatures near −190°c 535
Microscope examination of porous specimens, vacuum impregnation (N) 160
Microscope *see also* Electron microscope, Field ion microscope
Microscopy, field emission, fast recording for data for Fowler–Nordheim plots (N) 1051
Microspectrophotometer, design and construction 577
Microwave amplifiers, new method of measuring a.m.–ph.m. conversion 593
Microwave receiver, 4 mm, for plasma scattering experiments 47
Microwaves used for the detection of flaws and measurement of erosion rates in material 699
Modulation, amplitude–phase, method of measuring conversion in microwave amplifiers 593
Moiré fringe measuring system, and digital output, use in a soft x-ray spectrometer 506
Moiré instruments 1008
Moiré technique for strain measurements, modifying a profile projector 908
Monochromator, Ebert-type plane grating 740
Monochromator, semi-automatic for the determination of excitation cross sections 153
Monochromator, wide aperture, low resolution (N) 220
Mössbauer experiments, linear velocity drive for spectrometer (N) 212
Mössbauer experiments, precision velocity generator 1001
Mössbauer spectrometer (N) 285

Nervous tissue, mammalian, chamber for maintaining isolated during electrical recording 1025
Network, square lattice resistance, with diagonal elements 514
Nitrogen *see also under* Liquid nitrogen
Noise, random, use to improve resolution in analogue-to-digital voltage conversion (N) 1029
Nuclear instrumentation at the Physics Exhibition 668
Nuclear magnetic resonance in ferromagnetic materials, automatic swept-frequency spin-echo spectrometer 761
Nuclear magnetic resonance, pulse, analogue-to-digital converter (N) 635
Nuclear magnetic resonance detection, improved circuit (N) 391
Nuclear magnetic resonance probe, wide-range nuvistor (N) 299
Nuclear magnetic resonance spectrometer, variable frequency transmission line, with servo-correction background 349
Nuclear magnetic resonance studies, rotatable low temperature crystal holder (N) 1028
Nuclear quadrupole resonance detector, coaxial bridge with helical line sample holders 911
Nuclear quadrupole resonance spectra, time-averaged, elimination of baseline slope (N) 875
Nuclear resonance circuit, matching to an amplifier with application to pure quadrupole resonance (N) 475
Observatory, magnetotelluric, digital portable 943
Optical calibration, accurate rotary table of simple construction (N) 400
Optical incremental shaft resolver using plastic radial gratings 146
Optical magnetic probe 265
Optical plummet 744
Optical properties of alloys in ultra-high vacuum measurement 993
Optical shaft resolved using coupled light-modulators 269
Optical studies at temperatures down to 2°K with metal immersion cryostat 271
Optical transfer functions, new method for measurement 195
Optical transmission of thin absorbing films containing pinholes (N) 805
Optical transmission through windows set near Brewster angle 720
Optics of laser streak interferometry 725
Optics: measurement of aspherical surfaces 1005
Optics at the Physics Exhibition 666
Organic compounds, irradiated, sample injection port for gas–liquid chromatographic analysis (N) 1031
Oscilloscope, used for measuring thermoelectric figure of merit (N) 551

Particle size comparator 615
Particle size sensor, 'on-stream' x-ray 611
Particle track and beam envelope, small versatile analogue computer 697
Particles, irregularly shaped, experimental indication of the volume proportional response of the Coulter counter (N) 648
Pendulum, torsional, continuous recording of damping at constant altitude (N) 169
Permittivity and loss up to 5 GHz, bridge for measurement (N) 401
Phase changes at elevated temperatures, magnetic device for detection 200
Phase detector with improved selectivity (N) 62
Phase objects, scope and limitations of three-dimensional holography 1011
Photochemical reactor for quantitative studies (N) 483
Photodetectors, fast, measurement of time constants using an InAs laser 419
Photoelectric device for use in automatic Toepler pump (N) 473
Photographic method for the recording of specimen behaviour during rapid fracture tests (N) 873
Photography of field-ion microscope images (N) 223
Photography of transient events, recent work 321
Photoionization sources for mass spectrometers 283
Photolysis *see* Flash photolysis
Photomicrographs, use of paper negatives in production (N) 58
Photomultiplier, RCA 7265, single electron response (N) 797
Photomultiplier cooling apparatus 631
Photomultiplier tubes, reduction of noise and dark current by magnetic defocusing (N) 182
Photon counting with a soft x-ray spectrometer using a resistance strip magnetic electron multipler 21
Photoresist spinner, simple design (N) 655
Phototransducer for measuring relatively small angles (N) 479
Physics exhibition 665
Plasma furnace, rotating wall, d.c. arc discharge 525
Plasma scattering experiments, simple 4 mm microwave receiver 47
Plastic disks, small, preparation in large quantities (N) 656
Plug and socket connector, simple 50 kv feed-through (N) 1056
Point-count analysis, improved reticule ruling (N) 215
Pology raphy, impedance measurements: apparatus for accurate wide frequency work 843
Polarimeter, skylight, modified (N) 478
Pole figures, quantitative, device for automatic recording (N) 225
Polishing of thin single crystal layers (N) 159
Pontentiometer, digital trace reading (N) 951
Pore size distribution measurement in solids, automatic control 922
Porous specimens, vacuum impregnation prior to microscope examination (N) 160

Potential difference, contact, between conductive liquid phase, measurement by capacitor method 443
Powdered materials, improved electron bombardment evaporation source (N) 70
Powders excited by pulse ionizing radiation, luminescence spectrophotometer 584
Powders, fine, instrument for size analysis by x-ray absorption 606
Power amplifier, low-frequency, simple over-voltage protection device (N) 560
Preamplifiers, parametric and maser, used to improve sensitivity of e.p.r., spectrometers 430
Pressure cell, earth, influence of diaphragm flexibility on performance 781
Pressure differences, small, in liquids 254
Pressure differential gauge (N) 307
Pressure indicator, carbon paper 43
Pressure *see also* High pressure, Low pressure
Probe, anemonetric isokinetic, for sampling of aerosols 249
Probe, four point, minimizing errors of measurements of circular wafers 53
Probe, inductively loaded, for monitoring current pulses (N) 555
Probe, wide-range nuvistor n.m.r. (N) 299
Probe *see also* Magnetic probe
Profile projector for strain measurements using the moiré technique, modification 908
Proton channelling for crystal wafer orientation (N) 880
Pulse current transformer to check magnetron pulse current (N) 71
Pulses, random, efficient method of using an audio magnetic tape recorder for storing (N) 566
Pump, demountable glass circulation, with variable high pumping speed (N) 860
Pump, double-acting all-glass gas circulating (N) 388
Pump, gas-circulation, for laboratory (N) 213
Pump *see also* Toepler pump
Pyroelectric effect, infra-red radiation detection 694
Pyrometer, infra-red, for the measurement of nylon threadline temperatures (N) 1048
Pyrometer, infra-red radiation 988
Pyrometer *see also* Radiation pyrometers

Quadrupole resonance, application of matching a nuclear resonance circuit to an amplifier (N) 475
Quartz, small samples, determination by x-ray technique (N) 287
Quartz–metal sealed window, bakeable (N) 174, (L) 1059
Quartz spoon gauges, behaviour at elevated temperatures (N) 866

Radiation experiments, suppression of interference pulses (N) 792
Radiation pyrometers, calibration by black-body cavity (N) 221
Radio frequencies, measurement of surface impedance anomalies 278
Radioactive tracers used for the study of reactions in stationary droplets 936
Radiometer, biothermal: selection 847
Radiometer for continuous wave laser radiation (N) 218
Ratemeter correction procedures, validity and use (L) 241
Reactions, fast, in solution, study using microwave temperature-jump apparatus 449
Reactor, microcatalytic, precision method for measurement of small time intervals (N) 1046
Reactor, photochemical, for quantitative studies (N) 483
Reactor beam, automatic system for rapid measurement of irradiated thin foils 766
Recorder, multi-range, with a linear scale for conductivity measurements (N) 878
Recorder, simple device for converting single channel to multi-channel (N) 813
Recording system, digital magnetic 625
Rectifiers, silicon diffused-junction, used for a Cockcroft–Walton voltage multipler (N) 570
Reflectivity, infra-red, of microsamples, method for measuring (N) 65
Rejection-mask technique for the fabrication of cermet resisto (N) 313
Relay drive, transistorized selective, for standard times signa (N) 398
Reservoir, mercury, for McLeod gauges or cut-offs (N) 652
Resistors, cermet fabrication using a rejection-mask techniqu (N) 313
Resistors, nominally equal, inexpensive method for accurat comparison 633
Resonance *see under* Nuclear, Quadrupole
Resonators, helical, for spin measurement spectroscopy 509
Retardation lens used to improve abundance sensitivity for tandem mass spectrometer (N) 956
Reticule ruling, improved, for point-count analysis (N) 215
Rhenium from a thermal ionization source, isotopic analysis 76
Rheogoniometer, trifilar suspension 461
Ring specimens, small, apparatus for tensile testing 545
Road making materials, apparatus for testing resistance to fros damage (N) 553
Roads and soils, apparatus for measuring dynamic stiffness 537
Rotary table, accurate and simple, for optical calibration (N) 40

Salts, molten, phase equilibrium studies using high temperatur centrifuge 454
Sample holder, low temperature, with two degrees of freedom an a new method of measuring anisotropic susceptibilities 44
Scales, rational basis for design 93
Scintillator *see* Liquid scintillator
Seal, gas-tight thermobalance load (N) 791
Seal, static high pressure, low temperature (N) 962
Seal, vacuum-tight, bakeable, simple method for preparing silve chloride sheets (N) 172
Seal *see also* Vacuum seal
Seismometer, Willmore Mk II, electromagnetic calibration co (N) 1035
Semiconducting diamond, pulse method for measuring electrica resistance (N) 296
Semiconductor wafers, minimizing errors in four point prob measurements of resistivity 53
Sequencer, improved programmed controller 831
Shaft resolver, optical, using coupled light-modulators 269
Shaft resolver, optical incremental, using plastic radial gratings 14
Shear strength of adhesive joints at high temperatures, apparatu for measuring and methods of constructing adhesive joint 457
Ship performance, measurement: Physics Exhibition discourse 70
Shock tube, electrically driven, single discharge control circui (N) 651
Shock tube windows, use of TPX plastic in the near ultra-viole (N) 559
Shutter, capping, high speed 151
SI units 243
Silver chloride sheets, method for preparing for bakeable vacuum- tight seals (N) 172
Size analysis of fine powders by x-ray absorption 606
Skylight polarimeter, modified (N) 478
Soils and roads, apparatus for measuring dynamic stiffness 537
Solids, lump, apparatus for determination of apparent densities a elevated temperatures (N) 568
Solutions, aqueous, electrolytic conductance studies at elevated temperatures and pressures (N) 1037
Solutions, volatile, simple optical cell for measuring the spectra o small amounts under pressure at temperatures up to 300°C (N) 876
Sound propagation constants at low temperatures, device for measurement 136
Spark gap, low induction (N) 571
Spark gap, low-induction high-current, parallel operation without transit time isolation 599
Spark gap, subnanosecond 786
Spark-machining of photoconductive indium antimonide 973
Spectra of aurora, ultra-violet, high luminosity spectrograph for recording 357

Spectra, n.q.r., time-averaged, elimination of baseline slope (N) 875
Spectra, rapidly changing, study using computer of average transients 821
Spectra of small amounts of volatile solutions, simple optical cell for measuring under pressure at temperatures up to 300°C (N) 876
Spectra, Snoek, of metal wires at low frequencies, accurate recording (N) 810
Spectral analysis with a ten-channel fibre optic Fabry–Pérot fringe splitter 26
Spectroflash unit, versatile, with triggered spark gap (N) 76
Spectrograph, high luminosity, for recording the far ultra-violet spectra of aurora 357
Spectrography, infra-red, cell for study of adsorption (N) 961
Spectrometer, automatic swept-frequency, spin-echo for n.m.r. in ferromagnetic materials 761
Spectrometer, e.p.r., sensitivity using parametric and maser pre-amplifiers 430
Spectrometer, e.s.r., 280 MHz 433
Spectrometer, e.s.r., 900 MHz induction 437
Spectrometer, lens beta, photo-fabrication of a ring focus baffle (N) 474
Spectrometer, Mössbauer (N) 285
Spectrometer, Mössbauer, with linear velocity drive (N) 212
Spectrometer, sensitive 8 mm e.s.r., using double sideband demodulation 354
Spectrometer, soft x-ray, use of a moiré fringe measuring system and digital output 506
Spectrometer, soft x-ray, with photon counting using a resistance strip magnetic electron multiplier 21
Spectrometer, variable frequency transmission line n.m.r., with servo-correction of background 349
Spectrometer *see also* Mass spectrometer
Spectrometry, infra-red, modified halide-disk holder (N) 168
Spectrophotometer, luminescence, for powders excited by pulse ionizing radiation 584
Spectrophotometer, 12-channel Doppler-profile, for plasma-scattered laser light 690
Spectrophotometer *see also* Microspectrophotometer
Spectroscopy, atomic absorption, modulator for hollow cathode lamps (N) 1050
Spectroscopy, e.s.r., improved circuit techniques (N) 403
Spectroscopy, spin resonance helical resonators 509
Sputtered spot pattern monitor, accurate 261
Square lattice resistance network with diagonal elements 514
Sticking probabilities of gases on metal films, some fundamental problems in measurement 327
Stiffness *see also* Dynamic stiffness
Strain gauge technique for determining elastic constants of solidified gases and liquids (N) 179
Strain measurements, using the moiré technique, modifying a profile projector 908
Stresses, transient, in liquids, measured by use of pressure bar (N) 564
Striations, moving, direct display of electron temperature variation 1023
Strontium, precise isotope abundance ratio measurements with a mass spectrometric dual collector 141
Sun compass for the direct determination of geographic north (N) 661
Surface charge measurement, used for examination of electrical properties of insulators 521
Surface impedance measurement of anomalies at radio frequencies 278
Surface studies with glass filaments (N) 228
Surface tension, some remarks on the accurate and absolute measurement by a vertical plate method 855
Superconducting magnets, magnetic field sweep (N) 949
Superconductors, measurement of critical currents by self-balancing current regulator (N) 793
Surveying, optical plummet 744
Switch, high speed constant current, for use with N.P.L. plasma–metal junction harmonic generator (N) 406
Synchros, brushless, use for frequency modulation 440

Tape recorder, audio magnetic, used for storing random pulses (N) 566
Temperature, uniform, design of furnaces 257
Temperature control using commercially available d.c. amplifiers (N) 573
Temperature differences, small, use of thermocoax Chromel–Alumel thermocouples for measurement (N) 1055
Temperature integrator, portable thermistor 55
Temperature-jump apparatus, microwave, for study of fast reactions in solution 449
Temperature measurement, accurate, of specimen in a thermobalance (N) 649
Temperature measurement by multivibrator bridge 531
Temperature *see also* Low temperature, High temperature
Tensile machines (Instron), self-aligning grip system (N) 389
Tensile samples, improved method on nondestructive shaping (N) 308
Tensile test apparatus for small ring specimens 545
Texture goniometer, x-ray, used with device for the automatic recording of quantitative pole figures (N) 225
Thermal analysis, differential, at high pressure 839
Thermistor, low pressure measurement (N) 83
Thermistor, three terminal: the varitherm 775
Thermistor bridge for use in calorimetry (N) 290
Thermistor temperature integrator, portable 55
Thermobalance, techniques for accurate specimen temperature measurement (N) 649
Thermobalance-load seal, gas-tight (N) 791
Thermocouple, fixed point, calibration facility (N) 78
Thermocouple, thermocoax Chromel–Alumel, used for measurement of small temperature differences (N) 1055
Thermoelectric figure of merit, measurement using an oscilloscope (N) 551
Thermoluminescence dosimetry, measuring device 939
Thermoluminescent dosimetry systems, integrating, improved method of adjusting heating conditions (N) 481
Thin films *see under* Films
Time constants of current meters and turbine-type flowmeters, method of measuring 17
Time constants of some fast photodetectors measured using an InAs laser 419
Time signals, standard, transistorized selective relay drive (N) 398
Timing system: accurate synchronizing chronometer (N) 476
Tissue growth in rabbits' ears, device for the study of the effects of ultrasound (N) 165
Titanium and titanium alloys, preparation of thin foils for transmission electron microscopy (N) 63
Toepler pump, automatic, using a photoelectric device (N) 473
Toepler pump, improved automatic, for a gas measurement system (N) 1033
Trace-cutting attachment for a potentiometric chart recorder (N) 293
Transfer functions *see* Optical transfer functions
Transfer system, automatic, for liquid nitrogen 156
Transient events, recent work on photography 321
Transistor circuit design: 100kHz components for e.s.r. instrumentation (L) 882
Tubes, non-circular, simple vacuum seal (N) 561
Tungsten shadow casting for electron microscopical specimens 207
Tungsten specimens, contamination-free, preparation, for the field ion microscope (N) 1044
Turbine flowmeter and current meter, method of measuring time constants 17
Turbine flowmeter, miniature, for low flow rates 12

Ultrasound, device for the study of effects on tissue growth in rabbits' ears (N) 165
Underwater acoustics: Physics Exhibition discourse 709

Vacuum, ultra-high, channel multiplier, life tests (N) 1053
Vacuum, ultra-high, measurement of optical properties of alloys 997
Vacuum impregnation of porous specimen prior to microscope examination (N) 160
Vacuum physics at the Physics Exhibition 673
Vacuum reed chopper, self-maintained 639
Vacuum seal, large rotary, for manual operation (N) 405
Vacuum seal for non-circular tubes (N) 561
Vacuum systems, ultra-high, liquid helium cooled trap (N) 73
Varitherm: novel three terminal thermistor 775
Velocity generator, precision, suitable for Mössbauer experiments 1001
Velocity measurements, holographic (N) 1032
Velocity meter, Bagnold, use in laboratory density current measurements 37
Velocities of shear and longitudinal waves, simultaneous determination under pressure 379
Viscometer–gelation timer, laboratory (N) 963
Voltage conversion, analogue-to-digital, use of random noise to improve resolution (N) 1029
Voltage multiplier, Cockcroft–Walton, new design using silicons diffused-junction rectifiers (N) 570
Voltage scanner, automatic, for peak switching mass spectrometer 427
Voltmeter, high impedance, inexpensive, for student use (N) 563
Visual adaptation instrument to study influence on apparent brightness using an interocular technique 413

Waveforms, high voltage transient, measurement by Kerr cell systems 688
Wavemeter, parallel wire resistance water, dynamic testing (N) 803
Waves, shear and longitudinal, apparatus for simultaneous determination of velocities under pressure 379
Weighing of samples with rough surfaces: cavity forces 275
Whole-body counter *see under* Counter
Window, sealed, bakeable quartz–metal (N) 174, (L) 1059
Wire specimens, thin, holders for viewing by the electron microscope (N) 238

Xenon arc, high-pressure, simple device for stabilizing output (N) 952
X-ray absorption for size analysis of fine powders 606
X-ray back reflection specimen holder for accurate comparison of lattice spacings (N) 67
X-ray diffractometer, single crystal, high temperature furnace (N) 183
X-ray diffraction, use of balanced filters 736
X-ray diffraction, goniometer head for adjustment of single crystals (N) 643
X-ray fibre diagrams, electronic device for spherical averaging (N) 236
X-ray generators, design of safety system (N) 1039
X-ray particle size sensor, 'on-stream' 611
X-ray powder camera, small bulk specimen holder (N) 1041
X-ray spectrometer *see under* Spectrometer
X-ray technique for the determination of quartz in small samples (N) 287
X rays, soft, detection in microanalysis by point anode proportional counters 983
X rays, ultra soft, diffraction by optimization of lead stearate crystals 976

Yttrium aluminium garnet: chemical thinning technique for the simultaneous preparation of foils for transmission electron microscopy (N) 862

ABRIDGED NOTES

Balsam, Saleya, as a substitute for Canada balsam 486
Concrete, retractory, casting 486
Gas cell frequency standard using rubidium 486
Magnetic field measurements, wide range 486
Mass spectrometer, CH4, modification for field ionization studies 816
Temperature jump apparatus, switching circuit 816
Vacuum windlass 816

AUTHORS

(N) denotes Note on Experimental Technique and Apparatus, (L) Letter to the Editor

Abowitz, G., and Cath, P. G.: Automatic liquid-nitrogen transfer system 156

Adam, J., with Bargery, C. J., and Rivière, J. C.: Specimen transfer device for an ultra-high vacuum field ion microscope 692

Adams, N., and Jackson, R.: A trifilar-suspension rheogoniometer 461

Adams, O., Klein, K., and Verheyden, L.: A bakeable quartz-metal sealed window (L) 1059

Akers, R. J.: A simple mass spectrometer inlet leak (N) 871

Alldred, J. C., and Scollar, I.: Square cross section coils for the production of uniform magnetic fields 755

Anderson, A., with Stevenson, D. G., and Hill, R.: Automatic control of pore size distribution measurements in solids 922

Andréu, P., with Rosa-Brusin, M., and Franeschette, M.: A precision method for the measurement of small time intervals in micro-catalytic reactors and in gas chromatography (N) 1046

Anson, D., and Godridge, A. M.: A simple method for measuring heat flux 541

Archbold, E., Burch, J. M., and Ennos, A. E.: The application of holography to the comparison of cylinder bores 489

Armistead, C. G., Hambleton, F. H., Hockey, J. A., and Stockton, J. W.: An infra-red cell for studying adsorbed species at the gas–solid interface (N) 872

Arnell, R. D.: A simple specimen holder for the accurate comparison of lattice spacings by x-ray back reflection (N) 67

Ashworth, T., and Michael, J. F.: An accurate synchronizing chronometer (N) 476

Aspley, R. J., with Hansford, R. N.: A small versatile analogue computer for particle tracks and beam envelopes 697

Aziz, R. A., with Lim, C. C., and Sawyer, D. J.: A cryopump for use in low temperature control (N) 68

Bailey, B. J., and Kellner, K.: A static high pressure low temperature seal (N) 962

Bairnsfather, H.: A precision micrometer capacitor (N) 59

Bairnsfather, H., with Clothier, W. K.: The guarded sphere as a gauging electrode in length metrology 931

Baker, F. S., and Chambers, J.: A fast recording of data for Fowler–Nordheim plots in field emission microscopy (N) 1051

Baker, F. S., and Pritchard, J.: A mercury reservoir for cut-offs or McLeod gauges (N) 652

Baker, S. C.: An Ebert-type plane grating monochromator 740

Balain, K. S., and Singh, Interjit: Simple design of a photoresist spinner (N) 655

Banbury, J. R., and Nixon, W. C.: The direct observation of domain structure and magnetic fields in the scanning electron microscope 889

Barakat, M. F.: A sample injection port for the gas–liquid chromatographic analysis of irradiated organic compounds (N) 1031

Bargery, C. J., Adam, J., and Rivière, J. C.: Specimen transfer device for an ultra-high vacuum field ion microscope 692

Barnaby, C. F., and Orton, R. J. J.: A whole-body animal counter using a liquid scintillator 495

Barnaby, C. F., and Smith, T.: Performance of a large-area whole-body counter 499

Barnes, J. C., and Thomson, A. J.: The design and construction of a microspectrophotometer 577

Barnes, P. M., Gruber, J. E., and James, T. E.: The parallel operation of low-inductance high-current spark gaps without transit time isolation 599

Barnett, M. E., and Nixon, W. C.: A mirror electron microscope using magnetic lenses 893

Barrault, M. R., and Kekez, M. M.: A simple subnanosecond spark gap 786

Barrault, M. R., with McCartan, J.: An optical magnetic probe 265

Barry, W.: An inexpensive high-impedance voltmeter for student use (N) 563

Bauer, H. H., with Britz, D.: Impedance measurements in polarography: apparatus for accurate wide-frequency work 843

Beach, A. D.: A 12-channel Doppler-profile spectrophotometer for plasma-scattered laser light 690

Béguin, J., with Hintermann, H. E.: Tungsten shadow casting for electron microscopical specimens 207

Bellau, R. V.: Self-balancing current regulator for measurement of critical currents of super-conductors (N) 793

Benedini, M.: Readings of small pressure differences in liquids 254

Bengi, H., and Thomas, J. G.: A digital trace treading poentiometer (N) 951

Bennée, N. W., and Butt, D. K.: The photofabrication of a ring focus baffle for a lens β spectrometer (N) 474

Berry, C. J.: Low pressure measurement with thermistors (N) 83

Bersis, D. S., and Karybakas, C. A.: A novel three terminal thermistor: the varitherm 777

Bevan, H., and Ricketts, R. E.: An infra-red pyrometer for the measurement of nylon threadline temperatures (N) 1048

Beynon, J., and Head, K.: The fabrication of cermet resistors using a rejection-mask technique (N) 313

Beynon, J. H., Fontaine, A. E., Turner, D. W., and Williams, A. E.: Photoionization sources for mass spectrometers 283

Bilello, J. C.: An improved method for nondestructive shaping of tensile samples (N) 308

Birss, R. R., and Hegarty, B. C.: A torque magnetometer for use at high pressures 621

Biswas, B. N., Datta, G., and Kundu, M.: Phase-locking method of measuring dielectric constant (N) 557

Bjorklund, S., Kellermeyer, G. L., McAvoy, N., and Filipescu, N.: Liquid laser cavities 947

Block, M., and Way, N. R.: A simple maximum pressure differential gauge (N) 307

Bode, W., and Fletcher, P. C.: Glass filaments for surface studies (N) 228

Bol, W.: The use of balanced filters in x-ray diffraction 736

Boothroyd, R. G.: An anemometric isokinetic sampling probe for aerosols 259

Bourke, P. J., and Dawson, R. W.: Investigation of the accuracy of the Goldsmith–Cox electrolytic hygrometer at the 10^{-6} atm level (N) 87

Bowen, H. C., Chenevix-Trench, T., Drackley, S. D., Faust, R. C., and Saunders, R. A.: On-line computer system for processing high resolution mass spectral data 343

Bowkett, K. M., with Nordén, H.: Electron microscope holders for viewing thin wire specimens and field ion microscope tips (N) 238

Boyes, E. D., and Elvin, C. D.: On the photography of field-ion microscope images (N) 223

Bradford, H. F., and Smith, A. R.: A chamber for maintaining isolated mammalian nervous tissue during electrical recording 1025

Bradley, A. A.: The determination of quartz in small samples by an x-ray technique (N) 287

Bradsell, R. D.: A high speed constant current switch for use with the National Physical Laboratory plasma–metal junction harmonic generator (N) 406

Brady, M. M.: Simple pulse current transformer to check magnetron pulse current (N) 71

Britz, D., and Bauer, H. H.: Impedance measurements in polarography: apparatus for accurate wide-frequency work 843

Broadbent, T. E.: A new design for a Cockcroft–Walton voltage multiplier using silicon diffused-junction rectifiers (N) 570

Broberg, E., with Lehtinen, B., and Dahné, L.: Electron microscope specimen holder for simultaneous straining, tilting and rotating of thin foils (N) 289

Brocher, E. F., and Retchkiman, B. S.: Dynamic testing of a parallel wire resistance water wavemeter (N) 803

Brookes, M. E., and Smith, R. W.: Device for athermal and isothermal electrical resistivity studies in the range −186 to 400°c (N) 75
Broom, R. F.: Optical transmission of thin absorbing films containing pinholes (N) 805
Brown, M. A. C. S., Porteous, P., and Solley, D. J.: Time constants of some fast photodetectors measured using an indium arsenide laser 419
Buckmaster, H. A., and Dering, J. C.: The sensitivity of electron paramagnetic resonance spectrometers using parametric and maser pre-amplifiers 430
Burch, J. M., with Archbold, E., and Ennos, A. E.: The application of holography to the comparison of cylinder bores 489
Burley, R. W., with Rattee, I. D., and Flower, J. R.: Note on the experimental application of electrical conductivity (N) 858
Butler, H.: The use of paper negatives in the production of photomicrographs (N) 58
Butler, L. R. P., with Scott, R. H.: A modulator for hollow cathode lamps used in atomic absorption spectroscopy (N) 1050
Butt, D. K., with Bennée, N. W.: The photofabrication of a ring focus baffle for a lens β spectrometer (N) 474
Butterworth, J., MacLaughlin, D. E., and Moss, B. C.: The use of random noise to improve resolution in analogue-to-digital voltage conversion (N) 1029

Caldin, E. F., and Crooks, J. E.: A microwave temperature-jump apparatus for the study of fast reaction in solution 449
Camp, R. C.: A new digital magnetic recording system 625
Campbell, J. K. R., Watson, L. M., and Fabian, D. J.: A soft x-ray spectrometer with photon counting using a resistance strip magnetic electron multiplier 21
Carlow, J. S., with Clark, P. E., and Nichol, A. W.: A precision velocity generator suitable for Mössbauer experiments 1001
Carr-Brion, K. G., and Mitchell, P. J.: An 'on-stream' x-ray particle-size sensor 611
Carroll, J. E., and Tearle, C. A.: A new method of measuring amplitude modulation–phase modulation conversion in microwave amplifiers 593
Carson, K. R., and Rudee, M. L.: An improved standard specimen for alignment of electron microscopes (N) 1036
Carter, T. J.: Thickness measurements in the electron microscope (N) 61
Cassell, J., and Jiggins, A. H.: A linear velocity drive for a Mössbauer spectrometer (N) 212
Cath, P. G., with Abowitz, G.: Automatic liquid-nitrogen transfer system 156
Cavell, E. A. S.: An improved bridge for the measurement of permittivity and loss up to 5 GHz (N) 401
Chadwick, V. J., and Dye, B. C.: A fluidic wall-attachment amplifier of improved sensitivity 683
Chambers, A., Pomfret, D., and Prutton, M.: A novel method for the measurement of crystal anisotropy in magnetic films (N) 181
Chambers, J., with Baker, F. S.: A fast recording of data for Fowler–Nordheim plots in field emission microscopy (N) 1051
Chang, T. H. P., and Nixon, W. C.: Electron beam formation of 800 Å wide aluminium lines (N) 231
Chapman, G. E., and Kelly, J. C.: An accurate sputtered spot pattern monitor 261
Charles, M. E., and Cooke, B. A.: Optimization of lead stearate crystals for the diffraction of ultra soft xrays 976
Chatfield, E. J.: A simple particle size comparator 615
Chatfield, E. J.: A technique for accurate specimen temperature measurement in a thermobalance (N) 649
Chenevix-Trench, T., with Bowen, H. C., Drackley, S. D., Faust, R. C., and Saunders, R. A.: On-line computer system for processing high resolution mass spectral data 343
Chirer, E. G.: Device for the automatic recording of quantitative pole figures (N) 225
Chrysochoides, N. G., with Mavroyannakis, E. G., and Zikides, C. C.: An automatic system for rapid measurement of thin foils irradiated in reactor beam 766
Ciarrocca, S., with Stuart, W. E., and Usher, M. J.: Stray field modulation effects in the rubidium magnetometer 618
Clampitt, R., and Dunning, W. J.: The kinetic energy of fragment ions produced by electron impact 336
Clapham, P. B., and Dew, G. D.: Surface-coated reference flats for testing fully aluminized surfaces by means of the Fizeau interferometer 899
Clark, B. A. J.: An optical plummet 744
Clark, J., and Sudbury, G. C.: An accurate rotary table of simple construction, suitable for optical calibration purposes (N) 400
Clark, P. E., Nichol, A. W., and Carlow, J. S.: A precision velocity generator suitable for Mössbauer experiments 1001
Clarke, A. L.: Density determinations on small liquid samples 382
Clayton, B. R., and Massey, B. S.: Flow visualization in water: a review of techniqes 2
Cleaver, J. S.: A new high pressure ionization gauge. 969
Clothier, W. C.: Microscope for use at temperature near −190°c 535
Clothier, W. K., and Bairnsfather, H.: The guarded sphere as a gauging electrode in length metrology 931
Coleman, K. R.: Some recent work on the photography of transient events 321
Collins, A. T.: A method for measuring the infra-red reflectivity of microsamples (N) 65
Cooke, B. A., with Charles, M. E.: Optimization of lead stearate crystals for the diffraction of ultra soft x rays 976
Cooper, R., and Kamphausen, H. A.: Thin glass windows for use in fast electron irradiation vessels (N) 306
Collingwood, J. C., and White, J. W.: Helical resonators for spin resonance spectroscopy 509
Conlin, S. G., Levene, W. J., and Volume, W. F.: An instrument for size analysis of fine powders by x-ray absorption 606
Cox, L. C., with Goldsmith, P.: An improved electrolytic hygrometer 29
Creer, K. M., de Sa, A., and O'Reilly, W.: New vibrating sample magnetometers for use between 4 and 1000°K 133
Croft, W. J.: Device for the accurate orientation and fabrication of crystals (N) 1042
Crooks, J. E., with Caldin, E. F.: A microwave temperature-jump apparatus for the study of fast reaction in solution 449
Cross, J. D., Read, F. H., and Riddle, E. A.: Electron optical systems with fixed image positions for beams of variable energy 993
Curtis, G. H., Ferrier, R. P., and Murray, R. T.: An improved technique for ultra-high resolution electron diffraction (N) 867

Dahné, L., with Lehtinen, B., and Broberg, E.: Electron microscope specimen holder for simultaneous straining, tilting and rotating of thin foils (N) 289
Daly, N. R., with Freeman, N. J.: An improved abundance sensitivity for a tandem mass spectrometer by means of a retardation lens (N) 956
Daříček, T., with Hamal, K., Sochor, V., and Novotný, A.: Comparison of rotating mirror and liquid bleacher as a Q switch for a ruby laser (N) 548
Datars, W. R., with Vanderkooy, J., and Moss, J. S.: Magnetic field sweep for superconducting magnets (N) 949
Datta, G., with Biswas, B. N., and Kundu, M.: Phase-locking method of measuring dielectric constant (N) 557
Davies, D. K.: The examination of the electrical properties of insulators by surface change measurement 521
Davies, R. A., with Gidley, J. A. F.: A simple method of preparing thin metal foils for transmission electron microscope (N) 297
Dawaelheyns, A., with Ruland, W.: Electronic device for the spherical averaging of x-ray fibre diagrams (N) 236
Dawson, R. W., with Bourke, P. J.: Investigation of the accuracy of the Goldsmith–Cox electrolytic hygrometer at the 10^{-6} atm level (N) 87
Dean, D. S., and Green, D. T.: The use of microwaves for the detection of flaws and measurement of erosion rates in materials 699
Dean, R. H., Riedi, P. C., Scurlock, R. G., and Wilmshurst, T. H.: An automatic swept-frequency spin-echo spectrometer for nuclear magnetic resonance in ferromagnetic materials 761

Dearnaley, G., and Wilkins, M. A.: Crystal wafer orientation by proton chanelling (N) 880
van Deenen, P. J., with Schutten, J., de Haas, E. and de Heer, F. J.: A semi-automatic monochromator for the determination of excitation cross sections 153
Delavignette, P., with Sines, G.: An improved Valdré-type tilting holder for a Siemens electron microscope (N) 303
Delorme, J., with Perez, J., Peguin, P., and Gobin, P.: The continuous recording of damping of constant amplitude (N) 169
Dent, W. U., with Goldberg, A., and Miller, J. H.: A magnetic device for detecting phase changes at elevated temperatures 200
Derbyshire, W., with Stuart, J. P.: A phase detector with improved selectivity (N) 62
Dering, J. C., with Buckmaster, H. A.: The sensitivity of electron paramagnetic resonance spectrometers using parametric and maser preamplifiers 430
Deshpande, V. V., with Thatte, S. B.: A simple device for converting a single channel recorder to a multichannel recorder (N) 813
Dew, G. D., with Clapham, P. B.: Surface-coated reference flats for testing fully aluminized surfaces by means of the Fizeau interferometer 899
Devekey, R. C., and Majumdar, A. J.: A simple glass-fibre drawing apparatus (N) 864
Dimond, R. K., with Watson, L. M., and Fabian, D. J.: The use of a moiré fringe measuring system and digital output in a soft x-ray spectrometer 506
Dobson, G. R.: An apparatus for measuring the dynamic elastic properties of bitumens 375
Dodson, M. H.: Isotope ratio measurement by peak matching 775
Donaldson, I. G.: Theoretical consideration of a microflowmeter. 1018
Drackley, S. D., with Bowen, H. C., Chevenix-Trench, T., Faust, R. C., and Saunders, R. A.: On-line computer system for processing high resolution mass spectral data 343
Drinkwater, J. W.: Measurement of ship performance 702
Drouet, M. G.: Direct display of electron temperature variation in moving striations 1023
Dryburgh, P. M.: A glove-box and drying system for the manipulation of moisture sensitive materials (N) 658
Duffy, J., and Norbury, J. F.: A new micro-manometer 852
Dummer, G. W. A.: Materials and components at the Physics Exhibition 670
Duncan, S., and Lawson, F.: A double-acting all-glass gas circulating pump (N) 388
Duncan, W.: A 900 MHz induction electron spin resonance spectrometer 437
Dunn, M. H., and Maitland, A.: An inductively loaded probe for monitoring current pulses (N) 555
Dunning, W. J., with Clampitt, R.: The kinetic energy of fragment ions produced by electron impact 336
Duley, W. W.: A simple room temperature detector for use with carbon dioxide lasers 629
Dye, B. C., with Chadwick, V. J.: A fluidic wall-attachment amplifier of improved sensitivity 683
Dyson, Mary, with Pond, J.: A device for the study of the effects of ultrasound on tissue growth in rabbits' ears (N) 165

Eckhoff, R. K.: Experimental indication of the volume proportional response of the Coutler counter for irregularly shaped particles (N) 648
Eder, W. E., with Luxmoore, A. R.: Modifying a profile projector for strain measurements using the morié technique 908
Edgar, R. F., and Lawrenson, B.: A trace cutting attachment for a potentiometric chart recorder (N) 293
Edge, R. M.: A miniature turbine flowmeter for low flow rates 12
Edmonds, D. T., and Robinson, F. N. H.: On matching a nuclear resonance circuit to an amplifier with an application to pure quadrupole resonance (N) 475
Edwards, J. G.: An accurate carbon cone calorimeter for pulsed lasers 835
Edwards, J. G.: An automatic tracer of characteristic curves for optically pumped lasers (N) 309
Elvin, C. D., with Boyes, E. D.: On the photography of field-ion microscope images (N) 223
Endo, M., with Nagumo, M.: Preparation of thin metal foils from a small specimen for use in transmission electron microscopy (N) 550
Eng, R. S., with Leib, K. G.: Reactivation of a helium–neon laser by diffusion (N) 313
Ennos, A. E., with Archbold, E., and Burch, J. M.: The application of holography to the comparison of cylinder bores 489
Evans, D. M., and Mottram, A.: The introduction of trace amounts of dopant gases into continuous flow crystal growing systems (N) 176
Evans, S.: Fast scan mass spectrometry applied to gas chromatography 676
Everrett, J. E., and Hyndman, R. D.: A digital portable magneto-telluric observatory 943

Fabian, D. J., with Campbell, J. K. R., and Watson, L. M.: A soft x-ray spectrometer with photon counting using a resistance strip magnetic electron multiplier 21
Fabian, D. J., with Watson, L. M., and Dimond, R. K.: The use of a moiré fringe measuring system and digital output in a soft x-ray spectrometer 506
Farquhar, R. M., with Hayatsu, A.: A mass spectrometric dual collector for precise strontium isotope abundance ratio measurement 141
Fasth, J. E., Loberg, B., and Nordén, H.: Preparation of contamination-free tungsten specimens for the field-ion microscope (N) 1044
Faulkner, E. A., Grimbleby, J. B., and Wilmshurst, T. H.: Transistor circuit design: 100 kHz components for electron spin resonance instrumentation (L) 882
Faulkner, E. A., and Holman, A.: An improved circuit for nuclear magnetic resonance detection (N) 391
Faust, R. C., with Bowen, H. C., Chevenix-Trench, T., Drackley, S. D., and Saunders, R. A.: On-line computer system for processing high resolution mass spectral data 343
Fearn, D. G., and Wooding, E. R.: A low inductance spark gap (N) 571
Feibelman, W. A., with Frommhold, L.: The reduction of noise and dark current in photomultiplier tubes by magnetic defocusing (N) 182
Ferrier, R. P., with Curtis, G. H., and Murray, R. T.: An improved technique for ultra-high resolution electron diffraction (N) 867
Fietz, T. R.: Use of Bagnold's velocity meter in laboratory density current measurements 37
Filipescu, N., Bjorklund, S., Kellermeyer, G. L., and McAvoy, N.: Liquid laser cavities 947
Finegold, L.: Determination of mass of large gas volumes by direct weighing 789
Firth, E. W., and Ingram, D. J. E.: The use of a computer of average transients in the study of rapidly changing spectra 821
Fletcher, P. C., with Bode, W.: Glass filaments for surface studies (N) 228
Flower, J. R., with Rattee, I. D., and Burley, R. W.: Note on the experimental application of electrical conductivity (N) 858
Foa, E., Königsbuch, M., Lask, S., Schächter, O., and Stuhl, Z.: Apparatus for the study of reactions in stationary droplets by radioactive tracers 936
Fontaine, A. E., with Beynon, J. H., Turner, D. W., and Williams, A. E.: Photoionization sources for mass spectrometers 283
Foit, F. F., Jr, and Peacor, D. R.: A high temperature furnace for a single crystal x-ray diffractometer (N) 183
Forrest, J. R.: A simple flood protection device for cooling systems (N) 305
Forrest, M. J.: A ten-channel fibre Fabry–Pérot fringe splitter 26
Foulatier, R., et Fraissard, J.: Cellule pour étude de l'adsorption par spectrographie infra-rouge (N) 961
Fowler, R. G. with Wroe, H.: A simple 50 kv feed-through plug and socket connector (N) 1056
Fraissard, J., et Foulatier, R.: Cellule pour étude de l'adsorption par spectrographie infra-rouge (N) 961

Franeschette, M., with Rosa-Brusin, M., and Andréu, P.: A precision method for the measurement of small time intervals in micro-catalytic reactors and in gas chromatography (N) 1046
Fredericks, W. J.: A simple vacuum seal for non-circular tubes (N) 561
Freeman, N. J., and Daly, N. R.: An improved abundance sensitivity for a tandem mass spectrometer by means of a retardation lens (N) 956
Freyer, P., and Ohlenbusch, H.-D.: Measurements of contact potential differences between conductive liquid phases by the capacitor method 443
Friedman, H. A.: High temperature centrifuge for phase equilibrium studies in molten salts 454
Frommhold, L., and Feibelman, W. A.: The reduction of noise and dark current in photomultiplier tubes by magnetic defocusing (N) 182
Fujita, H., with Taoka, T., Kanaya, K., Iwanaga, M., and Iwasa, N.: Functional features of a 500 kv electron microscope 747
Fung, E., with Holman, W. R., and Stiles, E. B.: Tensile test apparatus for small ring specimens 545

Gallegos, E. J., and Klaver, R. F.: Automatic voltage scanner for a peak switching mass spectrometer 427
Gardiner, R. W., and Partridge, P. G.: Preparation of thin foils of titanium and titanium alloys for transmission electron microscopy (N) 63
Garside, D. H., with Smith, B. L.: Elastic constants of solidified gases and liquids by a strain gauge technique (N) 179
Gautschi, M., with Kesselring, P.: A coaxial bridge with helical line sample holders as a nuclear quadrupole resonance detector 911
Geake, J. E.: A diffraction grating calculator (N) 795
Geary, D. A., and Lemon, T. H.: The behaviour of quartz spoon gauges at elevated temperatures (N) 866
Gibbs, D. F., and Novaković, M. M.: Possibility of the detection of a conductor movement in a homogeneous magnetic field (L) 815
Gidley, J. A. F., and Davies, R. A.: A simple method of preparing thin metal foils for transmission electron microscopy (N) 297
Gobin, P., with Perez, J., Delorme, J., and Peguin, P.: The continuous recording of damping of constant amplitude (N) 169
Godridge, A. M., with Anson, D.: A simple method for measuring heat flux 541
Goldberg, A., Dent, W. U., and Miller, J. H.: A magnetic device for detecting phase changes at elevated temperatures 200
Goldsmid, H. J., with Symes, J.: Measurement of the thermoelectric figure of merit using an oscilloscope (N) 551
Goldsmith, P., and Cox, L. C.: An improved electrolytic hygrometer 29
Gordon, I., with Gray, P. S.: A pressurized Goldsmith–Cox hygrometer for plant use at ultra-low humidities (N) 84
Granger, D. E.: Vacuum impregnation of porous specimens prior to microscope examination (N) 160
Gray, P. S., and Gordon, I.: A pressurized Goldsmith–Cox hygrometer for plant use at ultra-low humidities (N) 84
Green, D. T., with Dean, D. S.: The use of microwaves for the detection of flaws and measurement of erosion rates in materials 699
Green, L., with Stewart, I. M.: Preparation of thin glass films for electron microscope examination by direct transmission (N) 216
Greenhow, R. C., with Schmidt, A. J.: An absolute method for measuring the energy output of a laser (N) 468
Grennberg, B.: A locus-sensitive proportional counter 203
Griffiths, T. R., Lee, F., and Wijayanayake, R. H.: A simple optical cell for measuring the spectra of small amounts of volatile solutions under pressure at temperatures up to 300°c (N) 876
Grimbleby, J. B., with Faulkner, E. A., and Wilmhurst, T. H.: Transistor circuit design: 100 kHz components for electron spin resonance instrumentation (L) 882
Gruber, J. E., with Barnes, P. M., and James, T. E.: The parallel operation of low-inductance high-current spark gaps without transit time isolation 599
Günthard, Hs. H., with Wild, U. P.: The design of a versatile spectroflash unit with a triggered spark gap (N) 76
Gustavsson, J. E.: A demountable glass circulation pump with variable, high pumping speed (N) 860

de Haas, E., with Schutten, J., van Deenen, P. J., and de Heer, F. J.: A semi-automatic monochromator for the determination of excitation cross sections 153
de Haas, J. R., van Ormondt, D., and Slottje, C.: A simple field tracking magnetometer for the range of 2000–4500 Oe (N) 471
Hadja, J.: The measurement of aspherical surfaces in optics 1005
Hall, J. A.: A design of furnace for very uniform temperatures 257
Hall, R.: Minimizing errors of four point probe measurements on circular wafers 53
Hamal, K., Sochor, V., Daříček, T., and Novotný, A.: Comparison of rotating mirror and liquid bleacher as a Q switch for a ruby laser (N) 548
Hambleton, F. H., with Armistead, C. G., Hockey, J. A., and Stockton, J. W.: An infra-red cell for studying adsorbed species at the gas–solid interface (N) 872
Händel, S. K.: An electrically insulating cold trap (N) 312
Hansford, R. N., and Aspley, R. J.: A small versatile analogue computer for particle tracks and beam envelopes 697
Hardy, J. A., and McCarroll, J. J.: The suppression of interference pulses in radiation experiments (N) 792
Hardy, J. A., Macnab, J. I., and Webb, G.: An electronic digital integrator (N) 959
Hardy, J. A., with Nancollas, G. H.: A thermistor bridge for use in calorimetry (N) 290
Hariharan, T. A.: A modified skylight polarimeter (N) 478
Harlick, N. G., and Hutton, D. R.: Wide range nuvistor nuclear magnetic resonance probe (N) 299
Harris, J.: Use of brushless synchros for frequency modulation 440
Haslett, R. W. G.: Underwater acoustics 709
Hayatsu, A., and Farquhar, R. M.: A mass spectrometric dual collector for precise strontium isotope abundance ratio measurements 141
Hayward, D. O., and Taylor, N.: Some fundamental problems in the measurement of sticking probabilities of gases on metal films 327
Head, K., with Beynon, J.: The fabrication of cermet resistors using a rejection-mask technique (N) 313
de Heer, F. P., with Schutten, J., van Deenen, P. J., and de Haas, E.: A semi-automatic monochromator for the determination of excitation cross sections 153
Hegarty, B. C., with Birss, R. R.: A torque magnetometer for use at high pressures 621
Henderson, J., with Williams, J. R.: A fixed thermocouple calibration facility (N) 78
Heppell, T. A.: A combined low energy and reflection high energy electron diffraction apparatus 686
Hill, D. W., and Powell, T.: Cross-sensitivity effects in non-dispersive infra-red analysers using condenser microphone detectors 189
Hill, D. W., and Powell, T.: The frequency response characteristics of some condenser microphone infra-red detectors 731
Hill, M. J., and Wyard, S. J.: A 280 MHz electron spin resonance spectrometer 433
Hillis, M. R.: A simple laboratory gas-circulation pump (N) 213
Hill, R., with Stevenson, D. G., and Anderson, A.: Automatic control of pore size distribution measurements in solids 922
Hindle, P. H., and Reay, N. K.: a control system for a fully automatic pressure scanned Fabry–Pérot interferometer 360
Hindle, P. H., Reay, N. K., and Ring, J.: A simple stable Fabry-Pérot etalon (N) 646
Hintermann, H. E., and Béguin, J.: Tungsten shadow casting for electron microscopical specimens 207
Hitchcock, J. A., with Northover, E. W.: A heat flux meter for use in boiler furnaces 371
Hockey, J. A., with Armistead, C. G., Hambleton, F. H., and Stockton, J. W.: An infra-red cell for studying adsorbed species at the gas–solid interface (N) 872

Hocking, M. G., with Vasantasree, V., and Pantony, D. A.: Gas-tight thermobalance-load seal (N) 791
Hodgetts, G. B., and Norman, D. E.: A laboratory viscometer–gelation timer (N) 963
Hodgson, T., with Mitchell, D., and Wyndham, C. H.: The selection of a biothermal radiometer 847
Holland, J. R.: Self-aligning grip system and tensile specimens for Instron machines (N) 389
Holman, A., with Faulkner, E. A.: An improved circuit for nuclear magnetic resonance detection (N) 391
Holman, W. R., Stiles, E. B., and Fung, E.: Tensile test apparatus for small ring specimens 545
Holmes, R., and Stott, M. A.: A device for the measurement of sound propagation constants at low temperatures 136
Hopkins, B. J., and Pender, K. R.: A liquid helium cooled trap for ultra-high vacuum systems (N) 73
Horszowski, S. M.: A pulse method for measuring the electrical resistance of semiconducting diamond (N) 296
Hotston, E. S.: A simple 4 mm microwave receiver for plasma scattering experiments 47
Howkins, D. S.: The carbon paper pressure indicator 43
Hren, J. J., with Newman, R. W., and Sanwald, R. C.: A method for indexing field ion micrographs 828
Hughes, G., with Ledwidge, T. J.: Gas density measurement by the natural damping of a vibrating reed 385
Humpidge, R. T., and Taylor, B. J.: Apparatus for measuring the shear strength of adhesive joints at high temperatures and methods for constructing the adhesive joints 457
Hunt, D. J.: Laser action in human breath and its use for monitoring the carbon dioxide content of air (N) 408
Hunt, M. D., Spittle, J. A., and Smith, R. W.: An acid saw for the strain-free cutting of single crystals (N) 230
Hui, S. W.: Measurement of surface impedance anomalies of radio frequencies 279
Hutton, D. R., with Harlick, N. G.: Wide range nuvistor nuclear magnetic resonance probe (N) 299
van Huyssteen, C. F.: A simple method for preparing silver chloride sheets for bakeable vacuum-tight seals (N) 172
Hydnman, R. D., with Everett, J. E.: A digital portable magneto-telluric observatory 943

Ingram, D. J. E., with Firth, E. W.: The use of a computer of average transients in the study ot rapidly changing spectra 821
Iwanaga, M., with Taoka, T., Fujita, H., Kanaya, K., and Iwasa, N.: Functional features of a 500 kv electron microscope 747
Iwasa, N., with Taoka, T., Fujita, H., Kanaya, K., and Iwanaga, M.: Functional features of a 500 kv electron microscope 747

Jackson, R., with Adams, N.: A trifilar-suspension rheogoniometer 461
James, T. E., with Barnes, P. M., and Gruber, J. E.: The parallel operation of low inductance high-current spark gaps without transit time isolation 599
Jefferies, D. K.: A small 180° fast scanning mass spectrometer 587
Jepson, P.: Method of measuring time constants of current meters and turbine-type flowmeters 17
Jevons, M.: Square lattice resistance networks with diagonal elements 514
Jewell, A. J.: Converting on–off controllers to proportional operation (N) 81
Jiggins, A. H., with Cassell, J.: A linear velocity drive for a Mössbauer spectrometer (N) 212
Johansson, M., with Lindskoug, B., Karlsson, R., and Kellgren, R.: Measuring device for thermoluminescence dosimetry 939
Johnston, D.: A dual-purpose glass blowing torch (N) 302
Jones, M. W., and Rigby, L. J.: Large rotary vacuum seals for manual operation (N) 405
Jones, R. P., with Kilvington, A. I., and Swift, J. D.: Effect of a.c. amplitude on the measurement of electron energy distribution functions 517

Kalibjian, R., and Tindall, W. E.: Electron beam profile indicator (N) 800
Kálmán, A.: On a new goniometer head (N) 643
Kamphausen, H. A., with Cooper, R.: Thin glass windows for use in fast electron irradiation vessels (N) 306
Kanaya, K., with Taoka, T., Fujita, H., Iwanaga, M., and Iwasa, N.: Functional features of a 500 kv electron microscope 747
Karlsson, R., with Lindskoug, B., Johansson, M., and Kellgren, R.: Measuring device for thermoluminescence dosimetry 939
Karybakas, C. A., with Bersis, D. S.: A novel three terminal thermistor: the varitherm 777
Keast, D. J.: A chemical thinning technique for the simultaneous preparation of foils for transmission electron microscopy: application to yttrium aluminium garnet (N) 862
Kekez, M. M., with Barrault, M. R.: A simple subnanosecond spark gap 786
Kellermeyer, G. L., with Bjorklund, S., McAvoy, N., and Filipescu, N.: Liquid laser cavities 947
Kellgren, R., with Lindskoug, R., Johansson, M., and Karlsson, R.: Measuring device for thermoluminescence dosimetry 939
Kellner, K., with Bailey, B. J.: A static high pressure low temperature seal (N) 962
Kelly, J. C., with Chapman, G. E.: An accurate sputtered spot pattern monitor 261
Kemplay, J. R., and Vernon, P.: An efficient method of using an audio magnetic tape recorder for storing random pulses (N) 566
Kennedy, S. W.: Detection of changes of lattice parameters around the interface in a crystal transformation (N) 812
Kesselring, P., and Gautschi, M.: A coaxial bridge with helical line sample holders as a nuclear quadrupole resonance detector 911
Kilvington, A. I., Jones, R. P., and Swift, J. D.: Effect of a.c. amplitude on the measurement of electron energy distribution functions 517
King, R. J.: Optics at the Physics Exhibition 666
Klaver, R. F., with Gallegos, E. J.: Automatic voltage scanner for a peak switching mass spectrometer 427
Klein, K., and Verheyden, L.: A bakeable quartz–metal sealed window (N) 174
Klein, K., and Verheyden, L.: Equipment for producing calibrated leaks especially adapted for substances with melting points above room temperature (N) 954
Klein, K. with Verheyden, L., and Adams, O.: A bakeable quartz–metal sealed window (L) 1059
Königsbuch, M., with Foa, E., Lask, S., Schächter, O., and Stuhl, Z.: Apparatus for the study of reactions in stationary droplets by radioactive tracers 936
Knight, R. B. D.: Progress in electronic instruments at the Physics Exhibition 672
Knox, J., with Williams, E. M., and Parham, D. V.: A metal immersion cryostat for optical studies of temperatures down to 2°K 271
Kundu, M., with Biswas, B. N., and Datta, G.: Phase-locking method of measuring dielectric constant (N) 557

Lask, S., with Foa, E., Königsbuch, M., Schächter, O., and Stuhl, Z.: Apparatus for the study of reactions in stationary droplets by radioactive tracers 936
Lawrenson, B., with Edgar, R. E.: A trace cutting attachment for a potentiometric chart recorder (N) 293
Lawson, F., with Duncan, S.: A double-acting all-glass gas cirulating pump (N) 388
Lawson, W. H.: A versatile thin film thickness monitor of high accuracy 917
Lee, F., with Griffiths, T. R., and Wijanayake, R. H.: A simple optical cell for measuring the spectra of small amounts of volatile solutions under pressure at temperatures up to 300°c (N) 876
Ledwidge, T. J., and Hughes, G: Gas density measurement by the natural damping ot a vibrating reed 385
Lehtinen, B.: Transmission electron microscope examination of cracks formed in massive bodies (N) 234
Lehtinen, B., Broberg, E., and Dahné, L: Electron microscope specimen holder for simultaneous straining, tilting and rotating of thin foils (N) 289

Leib, K. G., and Eng, R. S.: Reactivation of a helium–neon laser by diffusion (N) 313
Lemon, T. H., with Geary, D. A.: The behaviour of quartz spoon gauges at elevated temperatures (N) 866
Levene, W. J., with Conlin, S. G., and Volume, W. F.: An instrument for size analysis of fine powders by x-ray absorption 606
Lillicrap, S. C.: A luminescence spectrophotometer for powders excited by pulsed ionizing radiation 584
Lim, C. C., Aziz, R. A., and Sawyer, D. J.: A cryopump for use in low temperature control (N) 68
Lindskoug, B., Johansson, M., Karlsson, R., and Kellgren, R.: Measuring device for thermoluminescence dosimetry 939
Lingard, P. S., and Whitmore, R. L.: The preparation of small plastic disks in large quantities (N) 656
Lipton, A.: An improved programmed controller for sequential laboratory operations 831
Littlewood, A.: A multi-range recorder with a linear scale for conductivity measurements (N) 878
Loberg, B., with Fasth, J. E. and Norden, H.: Preparation of contamination-free tungsten specimens for the field-ion microscope (N) 1044
Lockyer, C.: A new interferometric method for measuring the thickness of thick films (N) 393
Lowde, N. A.: Simple glass flow switches (N) 173
Lown, D. A., and Wynne-Jones, Lord: An electrolytic conductance cell for use at elevated temperatures and pressures (N) 1037
Ludlow, J. H., Mitchell, W. H., Putley, E. H., and Shaw, N.: Infrared radiation detection by the pyroelectric effect 694
Lumley, J. L., with Wyngaard, J. C.: A constant temperature hot-wire anemometer 363
Luxmoore, A. R., and Eder, W. E.: Modifying a profile projector for strain measurements using the moiré technique 908

McAvoy, N., with Bjorklund, S., Kellermeyer, G. L., and Filipescu, N.: Liquid laser cavities 947
McCarroll, J. J., with Hardy, J. A.: The suppression of interference pulses in radiation experiments (N) 792
McCartan, J., and Barrault, M. R.: An optical magnetic probe 265
McGee, J. D., and Smith, R. W.: Gating problems in the dynamic electron image information store (L) 485
McIlraith, A. H., and Penfold, A. B.: A radial grating dividing engine of high accuracy 903
McLaren, K. G. and Williams, W. T.: An improved automatic Teopler pump for a gas measurement system. (N) 1033
MacLaughlin, D. E., with Butterworth, J. and Moss, B. C.: The use of random noise to improve resolution in analogue-to-digital voltage conversion (N) 1029
Macnab, J. I., with Hardy, J. A., and Webb, G.: An electronic digital integrator (N) 959
Maddock, A. J.: A rational basis for the design of scales 93
Maher, F. J.: The multivibrator bridge for temperature measurement 531
Mai, H., and Wagner, H.: Design for improvement of sensitivity of mass spectrographs (L) 883
Maitland, A., with Dunn, M. H.: An inductively loaded probe for monitoring current pulses (N) 555
Majumdar, A. J., with Devekey, R. C.: A simple glass-fibre drawing apparatus (N) 864
van Mal, H. H.: A low temperature sample holder with two degrees of freedom and a new method of measuring anisotropic susceptibilities 446
Massen, G. H , with Poulis, J. A.: The weighting of samples with rough surfaces: cavity forces 275
Massey, B. S., with Clayton, B. R.: Flow visualization in water: a review of techniques 2
Mavroyannakis, E. G., Zikides, C. C., and Chrysochoides, N. G.: An automatic system for rapid measurement of thin foils irradiated in reactor beam 766
May, A. D., with Timsit, R. S.: Design of air-core magnets for the generation of homegeneous fields 636
Mendelson, M.: A simple method of fabricating double-barrelled micropipette electrodes (N) 549
Meyer, R. T.: Apparatus for flash photolysis and time resolved mass spectrometry 422
Michael, J. F., with Ashworth, T.: An accurate synchronizing chronometer (N) 476
Miller, C. A.: A polytetrafluoroethylene die for pressing high purity materials (N) 565
Miller, C. A.: Temperature control using commercially available d.c. amplifiers (N) 573
Miller, J. H., with Goldberg, A., and Dent, W. U.: A magnetic device for detecting phase changes at elevated temperatures 200
Mitchell, D., Wyndham, C. H., and Hodgson, T.: The selection of a biothermal radiometer 847
Mitchell, P. J., with Carr-Brion, K.G.: An 'on-stream' x-ray particle-size sensor 611
Mitchell, W. H., with Ludlow, J. H., Putley, E. H., and Shaw, N.: Infra-red radiation detection by the pyroelectric effect 694
Monfils, A., and Vreux, J-M.: A high luminosity spectrograph for recording the far ultra-violet spectra of aurora 357
Morgan, R.: An automatic electropolishing supervisor for preparing field ion microscope specimens 808
Moss, B. C., with MacLaughlin, D. E., and Butterworth, J.: The use of random noise to improve resolution in analogue-to-digital conversion (N) 1029
Moss, J. S., with Vanderkooy, J., and Datars, W. R.: Magnetic field sweep for superconducting magnets (N) 949
Mottram, A., with Evans, D. M.: The introduction of trace amounts of dopant gases into continuous flow crystal growing systems (N) 176
Mulvey, T.: Vacuum and electron physics at the Physics Exhibition 673
Murray, R. T., with Curtis, G. H., and Ferrier, R. P.: An improved technique for ultra-high resolution electron diffraction (N) 867

Nagumo, M., and Endo, M.: Preparation of thin metal foils from a small specimen for use in transmission electron microscopy (N) 550
Nakamura, M., and Sasaki, T.: Some remarks on the accurate and absolute measurement of surface tension by a vertical plate method 855
Nancollas, G. H., and Hardy, J. A.: A thermistor bridge for use in calorimetry (N) 290
Napier, B. A., and Spencer, D. H. T.: An apparatus for the determination of the apparent densities of lump solids at elevated temperatures (N) 568
Nellist, G. R.: An apparatus for testing the resistance of road making materials to frost damage (N) 553
Ness, S., with Smith-Saville, R. J.: Photomultiplier cooling apparatus 631
Newey, C. W. A., with Pascoe, R. T., Radford, K. G., and Rawlings, R. D.: Instrumental modifications for compressive testing at temperatures up to 1800°C 366
Newman, R. W., Sanwald, R. C., and Hren, J. J.: A method for indexing field ion micrographs 828
Newton, S.: Kerr cell system for the measurement of high voltage transient waveforms 688
Nichol, A. W. with Clark, P. E. and Carlow, J. S.: A precision velocity generator suitable for Mössbauer experiments 1001
Niemelä, L.: An analogue-to-digital converter for pulsed nuclear magnetic resonance (N) 653
Nixon, W. C., with Banbury, J. R.: The direct observation of domain structure and magnetic fields in the scanning electron microscope 889
Nixon, W. C., with Barnett, M. E.: A mirror electron microscope using magnetic lenses 893
Nixon, W. C., with Chang, T. H. P.: Electron beam formation of 800 Å wide aluminium lines (N) 231
Norberg, S. G., Öberg, P. Å., and Wallin, B. G.: A simple electrometer tube holder (N) 74
Norbury, J. F., with Duffy, J.: A new micro-manometer 852
Nordén, H. and Bowkett, K. M.: Electron microscope holders for viewing thin wire specimens and field ion microscope tips (N) 238

Nordén, H., with Loberg, B. and Fasth, J. E.: Preparation of contamination-free tungsten specimens for the field-ion microscope (N) 1044
Norman, D. E., with Hodgetts, G. B.: A laboratory viscometer–gelation timer (N) 963
Northover, E. W., and Hitchcock, J. A.: A heat flux meter for use in boiler furnaces 371
Novaković, M.: Possibility of the detection of a conductor movement in a homogeneous magnetic field (L) 316
Novakovic, M., with Gibbs, D. F.: Possibility of the detection of a conductor movement in a homegoneous magnetic field (L) 815
Novotný, A., with Hamal, K., Sochor, V., and Daříček, T.: Comparison of rotating mirror and liquid bleacher as a *Q* switch for a ruby laser (N) 548

Öberg, P. Å., with Norberg, S. G., and Wallin, B. G.: A simple electrometer tube holder (N) 74
Öberg, P. Å., Persson, A., and Sjöstrand, U.: A high output impedance, low level d.c. amplifier utilizing a solid-state operational amplifier (N) 870
Ohlenbusch, H.-D., with Freyer, P.: Measurements of contact potential differences between conductive liquid phases by the capacitor method 443
van Oostrom, A.: Modulation of Bayard–Alpert ionization gauge with grid-end caps 927
O'Reilly, W., with Creer, K. M., and de Sa, A.: New vibrating sample magnetometers for use between 4 and 1000°K 133
van Ormondt, D., with de Haas, J. R., and Slottje, C.: A simple field tracking magnetometer for the range of 2000–4500 Oe (N) 471
Ormrod, G. T. W., and Patterson, W. R.: A self-maintained vacuum reed chopper 639
Orton, R. J. J., with Barnaby, C. F.: A whole-body animal counter using a liquid scintillator 495
Owston, C. N.: A Hall effect magnetometer for small magnetic fields (N) 798

Packwood, R. H. and Smith, R. W.: A spark-erosion machining device. (N) 1058
Pantony, D. A., with Vasantasree, V., and Hocking, M. G.: Gas-tight thermobalance-load seal (N) 791
Parham, D. V., with Williams, E. M., and Knox, J.: A metal immersion cryostat for optical studies of temperatures down to 2°K 271
Partridge, P. G., with Gardiner, R. W.: Preparation of thin foils of titanium and titanium alloys for transmission electron microscopy (N) 63
Pascoe, R. T., Radford, K. C., Rawlings, R. D., and Newey, C. W. A.: Instrumental modifications for compressive testing at temperatures up to 1800°C 366
Patankar, A. V.: A sensitive 8 mm electron spin resonance spectrometer using double sideband demodulation 354
Patterson, W. R., with Ormrod, G. T. W.: A self-maintained vacuum reed chopper 639
Peacor, D. R., with Foit, F. F., Jr,: A high temperature furnace for a single crystal x-ray diffractometer (N) 183
Pearl, P. R.: Single electron response of RCA 7265 photomultiplier 797
Peguin, P., with Perez, J., Delorme, J., and Gobin, P.: The continuous recording of damping of constant amplitude (N) 169
Pells, G. P.: Measurement of the optical properties of alloys in ultra-high vacuum 997
Pender, K. R., with Hopkins, B. J.: A liquid helium cooled trap for ultra-high vacuum systems (N) 73
Penfold, A. B., with McIlraith, A. H.: A radial grating dividing engine of high accuracy 903
Persson, A., with Öberg, P. Å., and Sjöstrand, U.: A high input impedance, low level d.c. amplifier utilizing a solid-state operational amplifier (N) 870
Perez, J., Delorme, J., Peguin, P., and Gobin, P.: The continuous recording of damping of constant amplitude (N) 169
Pick, U.: An improved electron bombardment evaporation source for powdered materials (N) 70
Pilgrim, D. H., with Watson, K. R., and Vincent, C. H.: Validity and use of ratemeter correction procedures (L) 241
Pimbley, W. T., with Speicher, C. A., and Wolff, C. W.: Cryogenically pumped all-metal field ion microscope (N) 167
Pirro, P.: The use of thermocoax Chromel–Alumel thermocouples for the measurement of small temperature differences (N) 1055
Pomfret, D., with Chambers, A., and Prutton, M.: A novel method for the measurement of crystal anisotropy in magnetic films (N) 181
Pond, J., and Dyson, Mary: A device for the study of the effects of ultrasound on tissue growth in rabbits' ears (N) 165
Porteous, P., with Brown, M. A. C. S., and Solley, D. J.: Time constants of some fast photodetectors measured using an indium arsenide laser 419
Poulis, J. A., and Massen, C. H.: The weighting of samples with rough surfaces: cavity forces 275
Powell, T., with Hill, D. W.: Cross-sensitivity effects in non-dispersive infra-red analysers using condenser microphone detectors 189
Powell, T., with Hill, D. W.: The frequency response characteristics of some condenser microphone infra-red detectors 731
Powell, W. J. A.: Spark-machining of photoconductive indium antomide 973
Pritchard, J., with Baker, F. S: A mercury reservoir for cut-offs or McLeod gauges (N) 652
Prutton, M., with Chambers, A., and Pomfret, D.: A novel method for the measurement of crystal anisotropy in magnetic films (N) 181
Putley, E. H., with Ludlow, J. H., Mitchell, W. H., and Shaw, N.; Infra-red radiation detection by the pyroelectric effect 694

Quinn, T. J.: A practical black-body cavity for the calibration of radiation pyrometers (N) 221

Radford, K. C., with Pascoe, R. T., Rawlings, R. D., and Newey, C. W. A.: Instrumental modifications for compressive testing at temperatures up to 1800°C 366
von Rahden, H. V. R.: A modified halide-disk holder for infra-red spectrometry 168
Rann, C. S.: Measurement of gas velocity in a flame (N) 227
Ranzetta, G. V. T., and Scott, V. D.: Point anode proportional counters for the detection of soft x-rays in microanalysis 983
Rattee, I. D., Flower, J. R., and Burley, R. W.: Note on the experimental application of electrical conductivity (N) 858
Ravid, E.: A single discharge control circuit for an electrically driven shock tube (N) 651
Rawlings, R., with Ritchie, J. G.: Recording accurate Snoek spectra of metal wires at low frequencies (N) 810
Rawlings, R. D., with Pascoe, R. T., Radford, K. C., and Newey, C. W. A.: Instrumental modifications for compressive testing at temperatures up to 1800°C 366
Read, F. H. with Cross, J. D. and Riddle, E. A.: Electron optical systems with fixed image positions for beams of variable energy 993
Read, T. B.: A water-cooled mercury arc for continuous wave laser pumping 273
Reay, N. K., with Hindle, P. H.: A control system for a fully automatic pressure scanned Fabry–Pérot interferometer 360
Reay, N. K., with Hindle, P. H., and Ring, J.: A simple stable Fabry–Pérot etalon (N) 646
Redman, J. D.: Holographic velocity measurement (N) 1032
Rees, A. A. T., and Roberts, G.: The use of T.P.X. plastic as shock tube windows in the near ultra-violet (N) 559
Rees, E. P., and Trevena, D. H.: The use of pressure-bar to measure transient stresses in liquids (N) 564
Retchkiman, V. S., with Brocher, E. F.: Dynamic testing of a parallel wire resistance water wavemeter (N) 803
Rice, D. A., and Roach, J.: An automatic Toepler pump using a photoelectric device (N) 473
Ricketts, R. E. with Bevan, H.: An infra-red pyrometer for the measurement of nylon threadline temperatures (N) 1048
Riddle, E. A. with Cross, J. D. and Read, F. H.: Electron optical systems with fixed image positions for beams of variable energy 993

Riedi, P. C., with Dean, R. H., Scurlock, R. G., and Wilmhurst, T. H.: An automatic swept-frequency spin-echo spectrometer for nuclear magnetic resonance in ferromagnetic materials 761
Rigby, L. J., with Jones, M. W.: Large rotary vacuum seals for manual operation (N) 405
Riley, G. H.: Isotopic analysis of rhenium from a thermal ionization source 769
Ring, J., with Hindle, P. H., and Reay, N. K.: A simple stable Fabry–Pérot etalon (N) 646
Ritchie, I. G., and Rawlings, R.: Recording accurate Snoek spectra of metal wires at low frequencies (N) 810
Rivière, J. C., Bargery, C. J., and Adam, J.: Specimen transfer device for an ultra-high vacuum field ion microscope 692
Roach, J., with Rice, D. A.: An automatic Toepler pump using a photoelectric device (N) 473
Roberts, G., with Rees, A. A. T.: The use of T.P.X. plastic as shock tube windows in the near ultra-violet (N) 559
Robinson, D. C.: Gas-tight metal foil windows (N) 392
Robinson, F. N. H., with Edmonds, D. T.: On matching a nuclear resonance circuit to an amplifier with an application to pure quadrupole resonance (N) 475
Rodgers, G. B.: Measurement of the projected area of dust samples (N) 217
Rosa-Brusin, M., Franeschette, M. and Andréu, P.: A precision method for the measurement of small time intervals in microcatalytic reactors and in gas chromatography (N) 1046
Rossouw, D. J., and van der Walt, A. J.: A transistorized selective relay drive for standard time signals (N) 396
Rudee, M. L., and Carson, K. R.: An improved standard specimen for alignment of electron microscopes (N) 1036
Ruland, W., and Dawaelheyns, A.: Electronic device for the spherical averaging of x-ray fibre diagrams (N) 236
Russell, A. D.: Differential thermal analysis of materials with very volatile components (N) 399

de Sa, A., with Creer, K. M., and O'Reilly, W.: New vibrating sample magnetometers for use between 4 and 1000°K 133
Sanwald, R. C., with Newman, R. W., and Hren, J. J.: A method for indexing field ion micrographs 828
Sasaki, T., with Nakamura, M.: Some remarks on the accurate and absolute measurement of surface tension by a vertical plate method 855
Saunders, J. E.: An instrument for the interocular matching of apparent brightness 413
Saunders, R. A., with Chevenix-Trench, T., Drackley, S. D., and Faust, R. C.: On-line computer system for processing high resolution mass spectral data 343
Savill, N. G., and Wall, W. F.: Differential thermal analysis at high pressure 839
Sawyer, D. J., with Lim, C. C., and Aziz, R. A.: A cryopump for use in low temperature control (N) 68
Schächter, O., with Foa, E., Königsbuch, M., Lask, S., and Stuhl, Z.: Apparatus for the study of reactions in stationary droplets by radioactive tracers 936
Scherr, H. J.: Phototransducer for measuring relatively small angles (N) 479
Schmidt, A. J., and Greenhow, R. C.: An absolute method for measuring the energy output of a laser (N) 468
Schumacher, D.: Versatile crystal for the study of point defects in quenched metals (N) 161
Schurer, J., and Stoelhorst, J.: A simple device for stabilizing the output of a high-pressure xenon arc (N) 952
Schutten, J., van Deenen, P. J., de Haas, E., and de Heer, F. J.: A semi-automatic monochromator for the determination of excitiation cross sections 153
Scott, R. H., and Butler, L. R. P.: A modulator for hollow cathode lamps used in atomic absorbtion spectroscopy (N) 1050
Scott, V. D. with Ranzetta, G. V. T.: Point anode proportional counters for the detection of soft x-rays in microanalysis 983
Scollar, I., with Alldred, J. C.: Square cross section coils for the production of uniform magnetic fields 755
Scurlock, R. G., with Dean, R. H., Riedi, P. C., and Wilmshurst, T. H.: An automatic swept-frequency spin-echo spectrometer for nuclear magnetic resonance in ferromagnetic materials 761
Scurlock, R. G., Utton, D. B., and Wilmshurst, T. H.: A variable frequency transmission line nuclear magnetic resonance spectrometer with servo-correction of background 349
Sharp, J. V.: A technique for the rapid measurement of thickness during the preparation of disk specimens for transmission electron microscopy (N) 292
Shaw, N., with Ludlow, J. H., Mitchell, W. H., and Putley, E. H.: Infra-red radiation detection by the pyroelectric effect 694
Sherwood, R. G.: An evaporation filament with automatic cut-off (N) 166
Sines, G., and Delavignette, P.: An improved Valdré-type tilting holder for a Siemens electron microscope (N) 303
Singh, Interjit, with Balain, K. S.: Simple design of a photoresist spinner (N) 655
Sjöstrand, U., with Öberg, P. Å., and Persson, A.: A high input impedance, low level d.c. amplifier utilizing a solid-state operational amplifier (N) 870
Skelton, W. J., and Wilson, W. R. D.: Axially ported high pressure intensifiers (N) 396
Slater, K.: The detection and measurement of dangerous quantities of carbon monoxide gas (N) 642
Slottje, C., with de Haas, J. R., and van Ormondt, D.: A simple field tracking magnetometer for the range of 2000–4500 Oe (N) 471
Smith, A. R. with Bradford, H. F.: A chamber for maintaining isolated mammalian nervous tissue during electrical recording 1025
Smith, B. L., and Garside, D. H.: Elastic constants of solidified gases and liquids by a strain gauge technique (N) 179
Smith, D. G.: Channel multiplier life tests in ultra-high vacuum (N) 1053
Smith, R. W., with Brookes, M. E.: Device for athermal and isothermal electrical resistivity studies in the range −186 to 400°C (N) 75
Smith, R. W. with Packwood, R. H.: A spark-erosion machining device (N) 1058
Smith, R. W., with Hunt, M. D., and Spittle, J. A.: An acid saw for the strain-free cutting of single crystals (N) 230
Smith, R. W., with McGee, J. D.: Gating problems in the dynamic electron image information store (L) 485
Smith, T., with Barnaby, C. F.: Performance of a large-area whole-body counter 499
Smith-Saville, R. J., and Ness, S.: Photomultiplier cooling apparatus 631
Sochor, V., with Hamal, K., Daříček, T., and Novotný, A.: Comparison of rotating mirror and liquid bleacher as a Q switch for a ruby laser (N) 548
Solley, D. J., with Brown, M.A.C.S., and Porteous, P.: Time constants of some fast photodetectors measured using an indium arsenide laser 419
Sparrow, R. W., with Tory, A. C.: The influence of diaphragm flexibility on the performance of an earth pressure cell 781
Speicher, C. A., Wolff, C. W., and Pimbley, W. T.: A cryogenically pumped all-metal field ion microscope (N) 167
Spencer, B. H. T., with Napier, B. A.: An apparatus for the determination of the apparent densities of lump solids at elevated temperatures (N) 568
Spencer, D. H. T.: A simple mercury cut-off for use in gas admission to evacuated systems (N) 295
Spittle, J. A., with Hunt, M. D., and Smith, R. W.: An acid saw for the strain-free cutting of single crystals (N) 230
Sporton, T. M.: Optical transmission through windows set near the Brewster angle 720
Stearn, J. W.: A radiometer for continuous wave laser radiation (N) 218
Stevenson, D. G., Hill, R., and Anderson, A.: Automatic control of pore size distribution measurements in solids 922
van Steveninck, J.: Apparatus for simultaneous determination of longitudinal and shear wave velocities under pressure 379

Stewart, I. M., and Green, L.: Preparation of thin glass films for electron microscope examination by direct transmission (N) 216
Stewart, I., and Sutton, D. J.: An electromagnetic calibration coil for a Willmore Mk II seismometer (N) 1035
Stiles, E. B., with Holman, W. R., and Fung, E.: Tensile test apparatus for small ring specimens 545
Stockton, J. W., with Armistead, C. G., Hambleton, F. H., and Hockey, J. A.: An infra-red cell for studying adsorbed species at the gas–solid interface (N) 872
Stoelhorst, J., with Schurer, J.: A simple device for stabilizing the output of a high-pressure xenon arc (N) 952
Stone, D. B.: A sun compass for the direct determination of geographic north (N) 661
Stott, M. A., with Holmes, R.: A device for the measurement of sound propagation constants at low temperatures 136
Stovell, J. E.: Dynamic viewing of high power CO_2 laser modes (N) 1045
Street, P. J., and Twamley, C. S.: A technique for flow visualization using chemical indicator solutions (N) 558
Stricker, S.: Inexpensive method for accurate comparison of nominally equal resistors 633
Stuart, J. P., and Derbyshire, W.: A phase detector with improved selectivity (N) 62
Stuart, J. P., with Warner, D.: An automatically controlled rotating head for single crystal studies (N) 869
Stuart, W. F., Ciarrocca, S., and Usher, M. J.: Stray field modulation effects in the rubidium magnetometer 618
Stuhl, Z., with Foa, E., Königsbuch, M., Lask, S., and Schächter, O.: Apparatus for the study of reaction in stationary droplets by radioactive tracers 936
Sudbury, G. C., with Clark, J.: An accurate rotary table of simple construction, suitable for optical calibration purposes (N) 400
Sutherland, H. H.: Design of a safety system for x-ray generators (N) 1039
Sutherland, J. C.: A novel method of making thin slits in metal foil (N) 1043
Sutton, D. J., with Stewart, I.: An electromagnetic calibration coil for a Willmore Mk II seismometer (N) 1035
Swift, J. D., with Kilvington, A. I., and Jones, R. P.: Effect of a.c. amplitude on the measurement of electron energy distribution functions 517
Sydenham, P. H.: An optical incremental shaft resolver using plastic radial gratings 146
Sydenham, P. H.: An optical shaft resolver using coupled light-modulators 269
Sydenham, P. H.: Precise automatic long length determination 465
Symes, J., and Goldsmid, H. J.: Measurement of the thermoelectric figure of merit using an oscilloscope (N) 551

Tanner, L. H.: The scope and limitations of three-dimensional holography of phase objects 1011
Tanner, L. H.: The optics of laser streak interferometry 725
Tanner, L. H.: The use of a ruby laser with interferometers suitable for work in fluid mechanics 1015
Taoka, T., Fujita, H., Kanaya, K., Iwanaga, M., and Iwasa, N.: Functional features of a 500 kv electron microscope 747
Taylor, B. J., with Humpidge, R. T.: Apparatus for measuring the shear strength of adhesive joints at high temperatures and methods for constructing the adhesive joints 457
Taylor, N., with Hayward, D. O.: Some fundamental problems in the measurement of sticking probabilities of gases on metal films 327
Taylor, T. B.: A high-speed capping shutter 151
Tearle, C. A., with Carroll, J. E.: A new method of measuring amplitude modulation–phase modulation conversion in microwave amplifiers 593
Thatte, S. B., and Deshpande, V. V.: A simple device for converting a single channel recorder to a multichannel recorder (N) 813
Thomas, J. G., with Bengi, H.: A digital trace reading potentiometer (N) 951
Thomson, A. J., with Barnes, J. C.: The design and construction of a microscpectrophotometer 577
Thorton, P. R., with Wayte, R. C.: A specimen cooling stage for the scanning electron microscope (N) 806
Thrower, E. N.: An apparatus for measuring the dyanamic stiffness of roads and soils 537
Timsit, R. S., and May, A. D.: Design of air-core magnets for the generation of homogeneous fields 636
Tindall, W. E., with Kalibjian, R.: Electron beam profile indicator (N) 800
Tong, D. A.: Elimination of baseline in time-averaged nuclear quadrupole resonance spectra (N) 875
Tory, A. C., and Sparrow, R. W.: The influence of diaphragm flexibility on the performance of an earth pressure cell 781
Trevena, D. H., with Rees, E. P.: The use of pressure-bar to measure transient stresses in liquids (N) 564
Tromp, F. M., and Wijnbergen, J. J.: Mass marker for the AEI mass spectrometer MS2H 209
Turner, D. W., with Beynon, J. H., Fontaine, A. E., and Williams, A. E.: Photoionization sources for mass spectrometers 283
Twamley, C. S., with Street, P. J.: A technique for flow visualization using chemical indicator solutions (N) 558

Ubbelohde, A. R.: Making electrical contacts to solid nonmetallic conductors (N) 645
Usher, M. J., with Stuart, W. F., and Ciarrocca, S.: Stray field modulation effects in the rubidium magnetometer 618
Utton, D. B., with Scurlock, R. G., and Wilmshurst, T. H.: A variable frequency transmission line nuclear magnetic resonance spectrometer with servo-correction of background 349

Vafiadakis, A. P.; Two moiré instruments 1008
VanCouvering, A., with Wittry, D. B.: A stereoscopic display system for electron microprobe instruments (N) 294
Vanderkooy, J., Moss, J. S., and Datars, W. R.: Magnetic field sweep for superconducting magnets (N) 949
Vasantasree, V., Pantony, D. A., and Hocking, M. G.: Gas-tight thermobalance-load seal (N) 791
Verheyden, L., with Klein, K.: A bakeable quartz–metal sealed window (N) 174
Verheyden, L., with Klein, K.: Equipment for producing calibrated leaks especially adapted for substances with melting points above room temperature (N) 954
Verheyden, L., with Klein, K. and Adams, O.: A bakeable quartz-metal sealed window (L) 1059
Vernon, P., with Kemplay, J. R.: An efficient method of using an audio magnetic tape recorder for storing random pulses (N) 566
Vincent, C. H., with Watson, K. R., and Pilgrim, D. H.: Validity and use of ratemeter correction procedures (L) 241
Volume, W. F., with Levene, W. J., and Conlin, S. G.: An instrument for size analysis of fine powders by x-ray absorption 606
Vreux, J-M., with Monfils, A.: A high luminosity spectrograph for recording the far ultra-violet spectra of aurora 357

Wadsworth, N. J.: A proton free-precession magnetometer for locating buried magnets (N) 552
Wagner, H., with Mai, H.: Design for improvement of sensitivity of mass spectrographs (L) 883
Wall, W. F., with Savill, N. G.: Differential thermal analysis at high pressure 839
Wallin, B. G., with Norberg, S. G., and Öberg, P. Å.: A simple electrometer tube holder (N) 74
Walling, J. C.: Low temperature techniques at the Physics Exhibition 671
van der Walt, A. J., with Rossouw, D. J.: A transistorized selective relay drive for standard time signals (N) 396
Ward, P. R.: A specimen airlock chamber for the Siemens Elmiskop I 681
Warner, D.: A rotatable low temperature crystal holder for nuclear magnetic resonance studies 1028
Warner, D., and Stuart, J. P.: An automatically controlled rotating head for single crystal studies (N) 869

Warwick, D. A., and Wells, C. H. J.: A photochemical reactor for quantitative studies (N) 483
Waterworth, M. D.: A new method for the measurement of optical transfer functions 195
Watson, K. R., Pilgrim, D. H., and Vincent, C. H.: Validity and use of ratemeter correction procedures (L) 241
Watson, L. M., with Cambell, J. K. R., and Fabian, D. J.: A soft x-ray spectrometer with photon counting using a resistance strip magnetic electron multiplier 21
Watson, L. M., Dimond, R. K., and Fabian, D. J.: The use of a moiré fringe measuring system and digital output in a soft x-ray spectrometer 506
Way, N. R., and Block, M.: A simple maximum pressure differential gauge (N) 307
Wayte, R. C., and Thornton, P. R.: A specimen cooling stage for the scanning electron microscope (N) 806
Weaving, G. S.: A portable thermistor integrator 55
Webb, G., with Hardy, J. A., and Macnab, J. F.: An electronic digital integrator (N) 959
Webb, G. A. M.: An improved method of adjusting the heating conditions of integrating thermoluminescent dosimetry systems (N) 481
Wells, C. H. J., with Warwick, D. A.: A photochemical reactor for quantitative studies (N) 483
Whitaker, A.: A small bulk specimen holder for x-ray powder camera (N) 1041
White, J. S.: An improved reticule ruling for point-counter analysis (N) 215
White, J. W., with Collingwood, J. C.: Helical resonators for spin resonance spectroscopy 509
White, R. A.: Atomic absorption method for the measurement of metal fumes 678
Whiting, J. S. S., and Williams, J. M.: f/1 low resolution monochromator (N) 220
Whitmell, D. S.: Gas contamination in a field-ion microscope pumped by sputter-ion pumps (N) 802
Whitmore, R. L., with Lingard, P. S.: The preparation of small plastic disks in large quantities (N) 656
Whyman, D.: A rotating-wall, d.c. arc plasma furnace 525
Wijayanayake, R. H., with Griffiths, T. R., and Lee, F.: A simple optical cell for measuring the spectra of small amounts of volatile solutions under pressure at temperatures up to 300°C (N) 876
Wijnbergen, J. J., with Tromp, F. M.: Mass marker for the AEI mass spectrometer MS2H 209
Wilbur-Ham, J.: A 100 kHz frequency shifter adjustable in steps of 1 in 10^{10} (N) 300
Wild, U. P., and Günthard, Hs. H.: The design of a versatile spectroflash unit with a triggered spark gap (N) 76
Wilkins, M. A., with Dearnaley, G.: Crystal wafer orientation by proton chanelling (N) 880
Williams, A. E., with Beynon, J. H., Fontaine, A. E., and Turner, D. W.: Photoionization sources for mass spectrometers 283
Williams, A. J.: The use of a radioactive beta source to monitor high airborne-dust concentrations (N) 562
Williams, D.: Nuclear instrumentation at the Physics Exhibition 668
Williams, E. W., Parham, D. V., and Knox, J.: A metal immersion cryostat for optical studies of temperatures down to 2°K 271
Williams, J. M., with Whiting, J. S. S.: f/1 low resolution monochromator (N) 220
Williams, J. R., and Henderson, J.: A fixed thermocouple calibration facility (N) 78
Williams, P.: An apparatus for the measurement of galvanic skin response 50
Williams, W. T. with MacLaren, K. G.: An improved automatic Teopler pump for a gas measurement system (N) 1033
Wilmshurst, T. H.: Some improved circuit techniques for electron spin resonance spectroscopy (N) 405
Wilmshurst, T. H., with Dean, R. H., Riedi, P. C., and Scurlock, R. G.: An automatic swept-frequency spin-echo spectrometer for nuclear magnetic resonance in ferromagnetic materials 761
Wilmshurst, T. H., with Faulkner, E. A., and Grimbleby, J. B: Transistor circuit design: 100 kHz components for electron spin resonance instrumentation (L) 882
Wilmshurst, T. H., with Scurlock, R. G., and Utton, D. B.: A variable frequency transmission line nuclear magnetic resonance spectrometer with servo-correction of background 349
Wilson, R. B.: Precision polishing of thin single crystal layers (N) 159
Wilson, W. R. D., with Skelton, W. J.: Axially ported high pressure intensifiers (N) 396
Wittry, D. B., and VanCouvering, A.: A stereoscopic display system for electron microprobe instruments (N) 294
Wolff, C. W., with Speicher, C. A., and Pimbley, W. T.: A cryogenically pumped all-metal field ion microscope (N) 167
Woodhams, F. W. D.: A simple Mössbauer, spectrometer (N) 285
Wooding, E. R., with Fearn, D. G.: A low inductance spark gap (N) 571
Wooster, G. A.: An improved goniometer head base for use on crystallographic apparatus (N) 178
Wraith, A. E.: A photographic method for the recording of specimen behaviour during rapid fracture tests (N) 873
Wright, B. M.: Centrifugal pumping of liquified gases (N) 469
Wright, P.; A simple over-voltage protection device for a low-frequency power amplifier (N) 560
Wroe, H. and Fowler, R. G.: A simple 50 kv feed-through plug and socket connector (N) 1056
Wyard, S. J., with Hill, M. J.: A 280 MHz electron spin resonance spectrometer 433
Wyndham, C. H., with Mitchell, D., and Hodgson, T.: The selection of a biothermal radiometer 847
Wyngaard, J. C., and Lumley, J. L.: A constant temperature hot-wire anemometer 363
Wynne-Jones, Lord, with Lown, D. A.: An electrolytic conductance cell for use at elevated temperatures and pressures (N) 1037

Young, R. S.: A new infra-red radiation pyrometer 988

Zastawny, A.: On a new formula for the gas amplification in a proportional counter (N) 395
Zikides, C. C., with Mavroyannakis, E. G., and Chrysochoides, N. G.: An automatic system for rapid measurement of thin foils irradiated in reactor beam 766

J. SCI. INSTRUM., 1966, VOL. 44

BOOK REVIEWS

Bergner, J., Gelbke, E., and Mehliss, W.: *Practical Photomicrography* 317
Borucki, L., and Dittmann, J.: *Digitale Messtechnik—Eine Einfuhrung* 90
Cox, A.: *Photographic Optics—A Focal Manual of Photo-Technique* 90
Gunter, W. A.: *The Physics of Modern Electronics* 1061
Hawley, R., and Maitland, A.: *Vacuum as an Insulator: An Indexed Bibliography* 817
Head, J. W.: *Mathematical Techniques in Electronics and Engineering Analysis* 1061
International Atomic Energy Agency: *Radioisotopes Instruments in Industry and Geophysics* 817
Markov, A. I.: *Ultrasonic Machining of Intractable Materials* 817
Murnaghan, F. D.: *Finite Deformation of an Elastic Solid* 1060
Pollister, A. W.: *Physical Techniques in Biological Research* 317
Roa, K. N.: Humphreys, C. J., and Rank, D. H.: *Wavelength Standards in the Infrared* 817
Reimer, L., *Electronenmikropische Untersuchunga- und Praparationsmethoden* 1060
Rogers, F. E.: *Topology and Matrices in the Solution of Networks* 1060
Saxe, R. F.: *High-Speed Photography* 90
Stoll, P.: *Experimentalle Methoden der Kernphysik* 317
Towers, T. D.: *Electronic Laboratory Instrument Practice* 817
White, G. W.: *Introduction to Microscopy* 817
Whittaker, E., and Robinson, G.: *The Calculus of Observations An Introduction to Numerical Analysis* 1060
Zabetakis, M. G.: *Safety with Cryogenic Fluids* 1060

PRINTED IN GREAT BRITAIN BY UNWIN BROTHERS LIMITED, WOKING AND LONDON (B333)

PAGE

Inexpensive method for accurate comparison of nominally equal resistors . . . . . S. STRICKER 633
Design of air-core magnets for the generation of homogeneous fields . . . R. S. TIMSIT and A. D. MAY 636
A self-maintained vacuum reed chopper . . . . . G. T. W. ORMROD and W. R. PATTERSON 639

NOTES ON EXPERIMENTAL TECHNIQUE AND APPARATUS

The detection and measurement of dangerous quantities of carbon monoxide gas . . . . . K. SLATER 642
On a new goniometer head . . . . A. KÁLMÁN 643
Making electrical contacts to solid nonmetallic conductors . . . . . A. R. UBBELOHDE 645
A simple, stable Fabry–Pérot etalon . . . . . P. H. HINDLE, N. K. REAY and J. RING 646
Experimental indication of the volume proportional response of the Coulter counter for irregularly shaped particles . . . . . K. ECKHOFF 648
A technique for accurate specimen temperature measurement in a thermobalance . . . E. J. CHATFIELD 649
A single discharge control circuit for an electrically driven shock tube . . . . . E. RAVID 651
A mercury reservoir for cut-offs or McLeod gauges . . . . . F. S. BAKER and J. PRITCHARD 652
An analogue-to-digital converter for pulsed nuclear resonance . . . . . L. NIEMELÄ 653
Simple design of a photoresist spinner . . . . . K. S. BALAIN and INTERJIT SINGH 655
The preparation of small plastic disks in large quantities . . . . . P. S. LINGARD and R. L. WHITMORE 656
A glove-box and drying system for the manipulation of moisture sensitive materials . . P. M. DRYBURGH 658
A sun compass for the direct determination of geographic north . . . . . D. B. STONE 661

Information: Conferences, lectures and exhibitions . . . 663

SEPTEMBER 1967

THE PHYSICS EXHIBITION 665–719

See page 665 for Contents

PAPERS

Optical transmission through windows set near the Brewster angle . . . . . T. M. SPORTON 720
The optics of laser streak interferometry L. H. TANNER 725
The frequency response characteristics of some condenser microphone infra-red detectors . . . . . D. W. HILL and T. POWELL 731
The use of balanced filters in x-ray diffraction. W. BOL 736
An Ebert-type plane grating monochromator S. C. BAKER 740
An optical plummet . . . . . B. A. J. CLARK 744
Functional features of a 500 kv electron microscope . . T. TAOKA, H. FUJITA, K. KANAYA, M. IWANAGA and N. IWASA 747
Square cross section coils for the production of uniform magnetic fields . . J. C. ALLDRED and I. SCOLLAR 755
An automatic swept-frequency spin-echo spectrometer for nuclear magnetic resonance in ferromagnetic materials . . . R. H. DEAN, P. C. RIEDI, R. G. SCURLOCK and T. H. WILMSHURST 761
An automatic system for rapid measurement of thin foils irradiated in reactor beam E. G. MAVROYANNAKIS, C. C. ZIKIDES and N. G. CHRYSOCHOIDES 766
Isotopic analysis of rhenium from a thermal ionization source . . . . . G. H. RILEY 769
Isotope ratio measurement by peak matching . . . . . M. H. DODSON 775

PAGE

A novel three terminal thermistor: the varitherm . . . . . D. S. BERSIS and C. A. KARYBAKAS 777
The influence of diaphragm flexibility on the performance of an earth pressure cell . . . . . A. C. TORY and R. W. SPARROW 781
A simple subnanosecond spark gap . . . . . M. R. BARRAULT and M. M. KEKEZ 786
Determination of mass of large gas volumes by direct weighing . . . . . L. FINEGOLD 789

NOTES ON EXPERIMENTAL TECHNIQUE AND APPARATUS

Gas-tight thermobalance-load seal . V. VASANTASREE, D. A. PANTONY and M. G. HOCKING 791
The suppression of interference pulses in radiation experiments . . J. A. HARDY and J. J. MCCARROLL 792
Self-balancing current regulator for measurement of critical currents of superconductors . R. V. BELLAU 793
A diffraction grating calculator . . . . J. E. GEAKE 795
Single electron response of RCA 7265 photomultiplier . . . . . P. R. PEARL 797
A Hall effect magnetometer for small magnetic fields . . . . . C. N. OWSTON 798
Electron beam profile indicator . . . . . R. KALIBJIAN and W. E. TINDALL 800
Gas contamination in a field-ion microscope pumped by sputter-ion pumps . . . . . D. S. WHITMELL 802
Dynamic testing of a parallel wire resistance water wavemeter . . E. F. BROCHER and B. S. RETCHKIMAN 803
Optical transmission of thin absorbing films containing pinholes . . . . . R. F. BROOM 805
A specimen cooling stage for the scanning electron microscope . . . R. C. WAYTE and P. R. THORNTON 806
An automatic electropolishing supervisor for preparing field ion microscope specimens . . R. MORGAN 808
Recording accurate Snoek spectra of metal wires at low frequencies . . J. G. RITCHIE and R. RAWLINGS 810
Detection of changes of lattice parameters around the interface in a crystal transformation. S. W. KENNEDY 812
A simple device for converting a single channel recorder to a multichannel recorder . . . . . S. B. THATTE and V. V. DESHPANDE 813

LETTERS TO THE EDITOR

Possibility of the detection of a conductor movement in a homogeneous magnetic field . . . . . D. F. GIBBS: M. M. NOVAKOVIĆ 815

Abridged notes 816
Book reviews 817
Information: Conferences, lectures and exhibitions . . . 818
New publications 819

OCTOBER 1967

PAPERS

The use of a computer of average transients in the study of rapidly changing spectra . . . . . E. W. FIRTH and D. J. E. INGRAM 821
A method for indexing field ion micrographs . . . . R. W. NEWMAN, R. C. SANWALD and J. J. HREN 828
An improved programmed controller for sequential laboratory operations . . . . . A. LIPTON 831
An accurate carbon cone calorimeter for pulsed lasers . . . . . J. G. EDWARDS 835
Differential thermal analysis at high pressure . . . . . N. G. SAVILL and W. F. WALL 839

PAGE

Impedance measurements in polarography: apparatus for accurate wide-frequency work . . . . . D. BRITZ and H. H. BAUER 843
The selection of a biothermal radiometer . . . . . D. MITCHELL, C. H. WYNDHAM and T. HODGSON 847
A new micro-manometer J. DUFFY and J. F. NORBURY 852
Some remarks on the accurate and absolute measurement of surface tension by a vertical plate method . . . . . M. NAKAMURA and T. SASAKI 855

NOTES ON EXPERIMENTAL TECHNIQUE AND APPARATUS

Note on the experimental application of electrical conductivity to tracer detection in fluid flow systems . . . I. D. RATTEE, J. R. FLOWER and R. W. BURLEY 858
A demountable glass circulation pump with variable, high pumping speed . . . . . J. E. GUSTAVSSON 860
A chemical thinning technique for the simultaneous preparation of foils for transmission electron microscopy: application to yttrium aluminium garnet D. J. KEAST 862
A simple glass-fibre drawing apparatus . . . . . R. C. DEVEKEY and A. J. MAJUMDAR 864
The behaviour of quartz spoon gauges at elevated temperatures . . . D. A. GEARY and T. H. LEMON 866
An improved technique for ultra-high resolution electron diffraction . . . . . G. H. CURTIS, R. P. FERRIER and R. T. MURRAY 867
An automatically controlled rotating head for single crystal studies . . D. WARNER and J. P. STUART 869
A high input impedance, low level d.c. amplifier utilizing a solid-state operational amplifier . . . . . P. Å. ÖBERG, A. PERSSON and U. SJÖSTRAND 870
A simple mass spectrometer inlet leak . . R. J. AKERS 871
An infra-red call for studying adsorbed species at the gas–solid interface . . . . . C. G. ARMISTEAD, F. H. HAMBLETON, J. A. HOCKEY and J. W. STOCKTON 872
A photographic method for the recording of specimen behaviour during rapid fracture tests A. E. WRAITH 873
Elimination of baseline slope in time-averaged nuclear quadrupole resonance spectra . . D. A. TONG 875
A simple optical cell for measuring the spectra of small amounts of volatile solutions under pressure at temperatures up to 300°C . . . . . T. R. GRIFFITHS, F. LEE and R. H. WIJAYANAYAKE 876
A multi-range recorder with a linear scale for conductivity measurements . . . . . A. LITTLEWOOD 878
Crystal wafer orientation by proton channelling . . . . . G. DEARNALEY and M. A. WILKINS 880

LETTERS TO THE EDITOR

Transistor circuit design: 100 kHz components for electron spin resonance instrumentation . E. A. FAULKNER and J. B. GRIMBLEBY; T. H. WILMSHURST 882
Design for improvement of sensitivity of mass spectrographs . . . . . H. MAI and H. WAGNER 883

Information: Conferences, lectures and exhibitions . . . 886
New publications 887

NOVEMBER 1967

PAPERS

The direct observation of domain structure and magnetic fields in the scanning electron microscope . . . . . J. R. BANBURY and W. C. NIXON 889
A mirror electron microscope using magnetic lenses . . . . . M. E. BARNETT and W. C. NIXON 893
Surface-coated reference flats for testing fully aluminized surfaces by means of the Fizeau interferometer . . . . . P. B. CLAPHAM and G. D. DEW 899

PAGE

A radial grating dividing engine of high accuracy . . . . . A. H. MCILRAITH and A. B. PENFOLD 903
Modifying a profile projector for strain measurements using the moiré technique . . . . . A. R. LUXMOORE and W. E. EDER 908
A coaxial bridge with helical line sample holders as a nuclear quadrupole resonance detector . . . . . P. KESSELRING and M. GAUTSCHI 911
A versatile thin film thickness monitor of high accuracy . . . . . W. H. LAWSON 917
Automatic control of pore size distribution measurements in solids D. G. STEVENSON, T. HILL and A. ANDERSON 922
Modulation of Bayard–Alpert ionization gauges with grid end-caps . . . . . A. VAN OOSTROM 927
The guarded sphere as a gauging electrode in length metrology . W. K. CLOTHIER and H. BAIRNSFATHER 931
Apparatus for the study of reactions in stationary droplets by radioactive tracers . . . . . E. FOA M. KÖNIGSBUCH, S. LASK, O. SCHÄCHTER and Z. STUHL 936
Measuring device for thermoluminescence dosimetry . . . . . B. LINDSKOUG, M. JOHANSSON, R. KARLSSON and R. KELLGREN 939
A digital portable magnetotelluric observatory . . . . . J. E. EVERETT and R. D. HYNDMAN 943
Liquid laser cavities . . . . . S. BJORKLUND, G. L. KELLERMEYER, N. MCAVOY and N. FILIPESCU 947

NOTES ON EXPERIMENTAL TECHNIQUE AND APPARATUS

Magnetic field sweep for superconducting magnets . . . J. VANDERKOOY, J. S. MOSS and W. R. DATARS 949
A digital trace reading potentiometer . . . . . H. BENGI and J. G. THOMAS 951
A simple device for stabilizing the output of a high-pressure xenon arc . J. SCHURER and J. STOELHORST 952
Equipment for producing calibrated leaks especially adapted for substances with melting points above room temperature . . . K. KLEIN and L. VERHEYDEN 954
An improved abundance sensitivity for a tandem mass spectrometer by means of a retardation lens . . . . . N. J. FREEMAN and N. R. DALY 956
An electronic digital integrator . . . . . J. A. HARDY, J. I. MACNAB and G. WEBB 959
Cellule pour étude de l'adsorption par spectrographie infra-rouge . . . R. FOULATIER et J. FRAISSARD 961
A static high pressure low temperature seal . . . . . B. J. BAILEY and K. KELLNER 962
A laboratory viscometer–gelation timer . . . . . G. B. HODGETTS and D. E. NORMAN 963

Information: Conferences, lectures and exhibitions . . . 966

DECEMBER 1967

PAPERS

A new high pressure ionization gauge . J. S. CLEAVER 969
Spark-machining of photoconductive indium antimonide . . . . . W. J. A. POWELL 973
Optimization of lead stearate cyrstals for the diffraction of ultra soft x rays M. W. CHARLES and B. A. COOKE 976
Point anode proportional counters for the detection of soft x rays in microanalysis . . . . . G. V. T. RANZETTA and V. D. SCOTT 983
A new infra-red radiation pyrometer . R. S. YOUNG 988
Electron optical systems with fixed image positions for beams of variable energy . . . . . J. D. CROSS, F. H. READ and E. A. RIDDLE 993

PAGE

Measurement of the optical properties of alloys in ultra-high vacuum . . . . . G. P. PELLS 997
A precision velocity generator suitable for Mössbauer experiments . . . . . P. E. CLARK, A. W. NICHOL and J. S. CARLOW 1001
The measurement of aspherical surfaces in optics . . . . . J. HAJDA 1005
Two moiré instruments . . . . A. P. VAFIADAKIS 1008
The scope and limitations of three-dimensional holography of phase objects . . . . L. H. TANNER 1011
The use of a ruby laser with interferometers suitable for work in fluid mechanics . . . . L. H. TANNER 1015
Theoretical consideration of a microflowmeter. . . . . I. G. DONALDSON 1018
Direct display of electron temperature variation in moving striations . . . . . M. G. DROUET 1023
A chamber for maintaining isolated mammalian nervous tissue during electrical recording . . . . . H. F. BRADFORD and A. R. SMITH 1025

NOTES ON EXPERIMENTAL TECHNIQUE AND APPARATUS

A rotatable low temperature crystal holder for nuclear magnetic resonance studies . . . D. WARNER 1028
The use of random noise to improve resolution in analogue-to-digital voltage conversion . . . . . J. BUTTERWORTH, D. E. MACLAUGHLIN and B. C. MOSS 1029
A sample injection port for the gas–liquid chromatographic analysis of irradiated organic compounds . . . . . M. E. BARAKAT 1031
Holographic velocity measurement . J. D. REDMAN 1032
An improved automatic Toepler pump for a gas measurement system . K. G. MCLAREN and W. T. WILLIAMS 1033
An electromagnetic calibration coil for a Willmore Mk II seismometer . . . I. STEWART and D. J. SUTTON 1035
An improved standard specimen for alignment of electron microscopes K. R. CARSON and M. L. RUDEE 1036
An electrolytic conductance cell for use at elevated temperatures and pressures . . . . . D. A. LOWN and LORD WYNNE-JONES 1037
Design of a safety system for x-ray generators . . . . . H. H. SUTHERLAND 1039
A small bulk specimen holder for x-ray powder camera . . . . . A. WHITAKER 1041
Device for the accurate orientation and fabrication of crystals . . . . . W. J. CROFT 1042

PAGE

A novel method of making thin slits in metal foil . . . . . J. C. SUTHERLAND 1043
Preparation of contamination-free tungsten specimens for the field-ion microscope . . . . . J. E. FASTH, B. LOBERG and H. NORDÉN 1044
Dynamic viewing of high power CO_2 laser modes . . . . . J. E. STOVELL 1045
A precision method for the measurement of small time intervals in microcatalytic reacters and in gas chromatography . . . . . M. ROSA-BRUSIN, M. FRANESCHETTE and P. ANDRÉU 1046
An infra-red pyrometer for the measurement of nylon threadline temperatures . . . . . H. BEVAN and R. E. RICKETTS 1048
A modulator for hollow cathode lamps used in atomic absorption spectroscopy . . . . . R. H. SCOTT and L. R. P. BUTLER 1050
The fast recording of data for Fowler–Nordheim plots in field emission microscopy . . . . . F. S. BAKER and J. CHAMBERS 1051
Channel multiplier life tests in ultra-high vacuum . . . . . D. G. SMITH 1053
The use of thermocoax Chromel–Alumel thermocouples for the measurement of small temperature differences . . . . . P. PIRRO 1055
A simple 50 kv feed-through plug and socket connector . . . . . H. WROE and R. G. FOWLER 1056
A spark–erosion machining device . . . . . R. H. PACKWOOD and R. W. SMITH 1058

LETTERS TO THE EDITOR

A bakeable quartz–metal sealed window . . . . . O. ADAMS: K. KLEIN and L. VERHEYDEN 1059

Book reviews 1060
Information: Conferences, lectures and exhibitions . . . 1062
New publications 1063
Miscellaneous 1063

SUBJECT INDEX TO VOLUME 44 1065
ABRIDGED NOTES INDEX TO VOLUME 44 . . . 1072
AUTHOR INDEX TO VOLUME 44 1073
BOOK REVIEW INDEX TO VOLUME 44 1083